

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**LEGRAND DALI LIGHTING MANAGEMENT SENSOR - 360° IR DUAL
DETECTION - SIDE RANGE 2 X 12 M**

Caracteristici tehnice
DALI lighting management sensors
Check presence and light level continuously, switch off when there is sufficient natural light
Manual switch-on and manual or automatic switch-off (factory setting)
Configuration tool Cat.No 0 882 30
Version for corridor
Fixes directly to a suspended ceiling with mounting claws (included) or installed in a 50 mm deep Batibox box Cat.No 0 893 58
Recommended fixing height: 2.5 m
360° infrared dual detection, side range 2 x 12 m
With switch-off warning and pilot light
IP 41
Optimum distance between 2 sensors: 20 m
Connection by automatic terminals
Surface mounted on ceiling using accessory Cat. No. 0 488 75
With 1 RJ 45 input
Supplied with RJ 45/BUS connector 16 V - 30 mA
Caracteristici generale
DALI management - for 1 or 2 circuits
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/dali-lighting-management-sensor-3600-ir-dual-detection-side-range-2-x-12-m-225166>