

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**LEGRAND DECLANSATOR ELECTRONIC MCCB - INTRERUPATOR
GENERAL TIP USOL 250 - ICU 36 KA 400 V~ - 3P - 40 A**

Caracteristici tehnice
MCCBs - fixed version
Protection against overloads:
I_r adjustable from 0.4 to 1 x I_n
t_r adjustable from 3 to 15s
Protection against short circuits:
I_{sd} adjustable from 1.5 to 10 x I_r
t_{sd} adjustable from 0 to 0.5s
Breaking capacity I_{cu} 36 kA (400 V~)
3P
I_n : 40 A
Caracteristici generale
DPX³ 250 electronic release - MCCBs from 40 to 250 A
Can be mounted on rail or on plate in XL³ cabinets and enclosures
MCCBs for switching, control isolation and protection of low Tensiune electrical lines
Supplied with fixing screws, connection plates for bars and cable lugs and insulated shields (phase barriers)
Can be fitted with cage terminals 120 mm² max. (flexible cable) or 150 mm² max. rigid cable and with DPX³ 160 and 250 common auxiliaries and accessories
Conform to IEC 60947-2
Pret: 3 538,57 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/declansator-electronic-mccb-intrerupator-general-tip-usol-250-icu-36-ka-400-v-3p-40-a-225221>