



Furnizor: **Sc Trivolt Distribution SRL** Reg. com.: J23/3300/2016 CIF: RO36421140 Adresa: Strada Apusului nr 3 (primul sens giratoriu Tehodor Pallady-Autostrada Soarelui), Catelu, Ilfov Banca: BRD IBAN: RO34BRDE441SV13182234410

Image: Control of the set of supplementary devices with the possibility of simple independent installation: State contact KSV47; Undervoltage trip RMM47; - Undervoltage release RN47. - Undevoltage release RN47.		IEK SIGURANTA AUTOMATA VA47-100 4P 35A 10KA CURBA C
 a ctive and inductive loads. Recommended for use in lead-in distributors of domestic and industrial electric installations. Two types of protection against overload and short circuit. Complete set of supplementary devices with the possibility of simple independent installation: State contact KS47; State contact KS47; Low-voltage release RN47; Indication of contact position. Latching on DIN-rail with double locking. Litching on DIN-rail with double locking. Wide operating temperature range from -40 to +50° Di; Updated wider engagement lever with improved contact area. Notches on contact terminals reduce heat loss and increase mechanical stability of the connection. Higher switching capacity of 10000A provides for installing VA47-100 as input circuit breaking capacity EN 60898; 10 Widt operating temperature range: 60 Rated short-circuit breaking capacity EN 60898; 10 Width in number of modular spacings; 6 Max. cross section incoming capacity: S Nominal voltage DC: ≤ 60 Rated surge voltage invariability: 6 Current limiting class: 3 Frequency: 50 Degree of protection (IP): EV006405 Ambient class: IEK V0000010 Number of poles: 4 Voltage type: EV000509 Built in dept: 74, 3 Type of electric connection: EV000415 Release actuating time in short-circuit tm zone: 0,1 Nominal rated voltage: 400 Nominal rate		IIIX GLOCIALITITATI COMMINATATI CON TE SUR LONA CONDA C
Complete set of supplementary devices with the possibility of simple independent installation: - State contact KS47; - State contact KS47; - State contact KS47; - State contact tSV47; - Low-voltage release RN47. Latching on DIN-rail with double locking. Latching on DIN-rail with double locking. Lude operating temperature range from -40 to +50° Đj. Updated wider engagement lever with improved contact area. Notches on contact terminals reduce heat loss and increase mechanical stability of the connection. Higher switching capacity of 10000A provides for installing VA47-100 as input circuit breakers.Number of poles: 4 Primary current: 35 Release characteristic: EV000084 Nominal operating voltage: 400 Rated short-circuit breaking capacity EN 60898: 10 Width in number of modular spacings: 6 Max cross section incoming cable: 35 Nominal voltage DC: ≤ 60 Rated surge voltage invariability: 6 Current limiting class: 3 Frequency: 50 Frequency: 50 Degree of protection (IP): EV006405 Ambient class: IEK V000010 Number of poles (total): 4 Voltage type: EV000509 Built-in depth: 74,3 Type of electric connection: EV000415 Release actuating time in short-circuit tm zone: 0,1 Nominal rated current: 35.0 Number of protected poles: 4 Pret: 0,00 lei (TOVA inclus) Detatli online: https://www.materialeelectrice.ro/siguranta-automata-va47-100-4p-35a-		active and inductive loads. Recommended for use in lead-in distributors of domestic and industrial electric installations. Two types of protection against overload and short
 - State contact KS47; - State contact KS47; - State contact ge trip RMM47; - Low-voltage release RN47. - Indication of contact position. Latching on DIN-rail with double locking. Wide operating temperature range from -40 to +50° Đ;. Updated wider engagement lever with improved contact area. Notches on contact terminals reduce heat loss and increase mechanical stability of the connection. Higher switching capacity of 10000A provides for installing VA47-100 as input circuit breakers. Number of poles: 4 Primary current: 35 Release characteristic: EV000084 Nominal operating voltage: 400 Rated short-circuit breaking capacity EN 60898: 10 Width in number of modular spacings: 6 Max. cross section incoming cable: 35 Nominal voltage DC: ≤ 60 Rate de surge voltage invariability: 6 Current limiting class: 3 Frequency: 50 Frequency: 50 Frequency: 50 Begree of protection: EV000610 Number of poles (total): 4 Voltage type: EV000509 Built-in depth: 74,3 Type of electric connection: EV000415 Release actuating time in short-circuit tm zone: 0,1 Nominal rade dvoltage: 400 Number of protected poles: 4 Preto, 0,00 lei (TVA inclus) Detatii online: https://www.materialeelectrice.ro/siguranta-automata-va47-100-4p-35a- 		Complete set of supplementary devices with the possibility of simple independent
 - Undervoltage trip RMM47; - Low-voltage release RN47. Indication of contact position. Latching on DIN-rail with double locking. Wide operating temperature range from -40 to +50° bj. Updated wider engagement lever with improved contact area. Notches on contact terminals reduce heat loss and increase mechanical stability of the connection. Higher switching capacity of 10000A provides for installing VA47-100 as input circuit breakers.Number of poles: 4 Primary current; 35 Release characteristic: EV000084 Nominal operating voltage: 400 Rated short-circuit breaking capacity EN 60898: 10 Width in number of modular spacings: 6 Max. cross section incoming cable: 35 Nominal voltage DC: ≤ 60 Rated surge voltage invariability: 6 Current limiting class: 3 Frequency: 50 Frequency: 50 Frequency: 50 Begree of protection (IP): EV006405 Ambient class: IEK V000010 Number of poles (total): 4 Voltage type: EV000509 Built-in depth: 74,3 Type of electric connection: EV00415 Release actuating time in short-circuit m zone: 0,1 Nominal rated voltage: 400 Number of protected poles: 4 Pret: 0,00 lei (TVA inclus) Detalii online: https://www.materialeelectrice.ro/siguranta-automata-va47-100-4p-35a- 		- State contact KS47;
Indication of contact position. Latching on DIN-rail with double locking. Wide operating temperature range from -40 to +50° Bj. Updated wider engagement lever with improved contact area. Notches on contact terminals reduce heat loss and increase mechanical stability of the connection. Higher switching capacity of 10000A provides for installing VA47-100 as input circuit breakers.Number of poles: 4 Primary current: 35 Release characteristic: EV000084 Nominal operating voltage: 400 Rated short-circuit breaking capacity EN 60898: 10 Width in number of modular spacings: 6 Max. cross section incoming cable: 35 Nominal voltage DC: ≤ 60 Rated surge voltage invariability: 6 Current limiting class: 3 Frequency: 50 Frequency: 50 Degree of protection (IP): EV006405 Ambient class: IEK V000010 Number of poles (total): 4 Voltage type: EV000509 Built-in depth: 74,3 Type of electric connection: EV000415 Release actuating time in short-circuit th zone: 0,1 Nominal rated voltage: 400 Number of protected poles: 4 Pret: 0,00 lei (TVA inclus) Detalli online: https://www.materialeelectrice.ro/siguranta-automata-va47-100-4p-35a-	100V- 10000	
Latching on DIN-rail with double locking. Wide operating temperature range from -40 to +50° Dj. Updated wider engagement lever with improved contact area. Notches on contact terminals reduce heat loss and increase mechanical stability of the connection. Higher switching capacity of 10000A provides for installing VA47-100 as input circuit breakers.Number of poles: 4 Primary current: 35 Release characteristic: EV000084 Nominal operating voltage: 400 Rated short-circuit breaking capacity EN 60898: 10 Width in number of modular spacings: 6 Max. cross section incoming cable: 35 Nominal voltage DC: ≤ 60 Rated surge voltage invariability: 6 Current limiting class: 3 Frequency: 50 Degree of protection (IP): EV006405 Ambient class: IEK_V000010 Number of poles (total): 4 Voltage type: EV000509 Built-in depth: 74.3 Type of electric connection: EV000415 Release acuating time in soft-circuit tm zone: 0,1 Nominal rated voltage: 400 Number of protected poles: 4 Pret: 0,00 lei (TVA inclus) Detalli online: https://www.materialeelectrice.ro/siguranta-automata-va47-100-4p-35a-	1 Provide Hill I Have	- Low-voltage release RN47.
2 4 6 8 Wide operating temperature range from -40 to +50° Đi. Updated wider engagement lever with improved contact area. Notches on contact terminals reduce heat loss and increase mechanical stability of the connection. Higher switching capacity of 10000A provides for installing VA47-100 as input circuit breakers.Number of poles: 4 Primary current: 35 Release characteristic: EV000084 Nominal operating voltage: 400 Rated short-circuit breaking capacity EN 60898: 10 Width in number of modular spacings: 6 Max. cross section incoming cable: 35 Nominal voltage DC: ≤ 60 Rated surge voltage invariability: 6 Current limiting class: 3 Frequency: 50 Frequency: 50 Pegree of protection (IP): EV006405 Ambient class: IEK_V000010 Number of poles (total): 4 Voltage type: EV000509 Built-in depth: 74,3 Type of electric connection: EV000415 Release actuating time in short-circuit tm zone: 0,1 Nominal rated voltage: 400 Number of protected poles: 4 Pret: 0,00 lei (TVA inclus) Detalii online: https://www.materialeelectrice.ro/siguranta-automata-va47-100-4p-35a-		
Updated wider engägement lever with improved contact area. Notches on contact terminals reduce heat loss and increase mechanical stability of the connection. Higher switching capacity of 10000A provides for installing VA47-100 as input circuit breakers.Number of poles: 4 Primary current: 35 Release characteristic: EV000084 Nominal operating voltage: 400 Rated short-circuit breaking capacity EN 60898: 10 Width in number of modular spacings: 6 Max. cross section incoming cable: 35 Nominal voltage DC: ≤ 60 Rated surge voltage invariability: 6 Current limiting class: 3 Frequency: 50 Frequency: 50 Degree of protection (IP): EV006405 Ambient class: IEK V0000010 Number of poles (total): 4 Voltage type: EV000509 Built-in depth: 74.3 Type of electric connection: EV000415 Release actuating time in short-circuit tm zone: 0,1 Nominal rated current: 35.0 Nominal rated voltage: 400 Number of protected poles: 4 Pret: 0,00 lei (TVA inclus) Detalii online: https://www.materialeelectrice.ro/siguranta-automata-va47-100-4p-35a-	3 2 3 4 3 6 3 8	Wide operating temperature range from -40 to $+50^{\circ}$ Đ _i .
 connection. Higher switching capacity of 10000A provides for installing VA47-100 as input circuit breakers. Number of poles: 4 Primary current: 35 Release characteristic: EV000084 Nominal operating voltage: 400 Rated short-circuit breaking capacity EN 60898: 10 Width in number of modular spacings: 6 Max. cross section incoming cable: 35 Nominal voltage DC: ≤ 60 Rated surge voltage invariability: 6 Current limiting class: 3 Frequency: 50 Frequency: 50 Prequency: 50 Degree of protection (IP): EV006405 Ambient class: IEK_V000010 Number of poles (total): 4 Voltage type: EV000509 Built-in depth: 74,3 Type of electric connection: EV000415 Release actuating time in short-circuit tm zone: 0,1 Nominal rated current: 35.0 Nominal rated voltage: 400 Number of poles: 40 Pret: 0,00 lei (TVA inclus) Detalii online: https://www.materialeelectrice.ro/siguranta-automata-va47-100-4p-35a- 		Updated wider engagement lever with improved contact area.
Higher switching capacity of 10000A provides for installing VA47-100 as input circuit breakers.Number of poles: 4 Primary current: 35 Release characteristic: EV000084 Nominal operating voltage: 400 Rated short-circuit breaking capacity EN 60898: 10 Width in number of modular spacings: 6 Max. cross section incoming cable: 35 Nominal voltage DC: ≤ 60 Rated surge voltage invariability: 6 Current limiting class: 3 Frequency: 50 Perequency: 50 Degree of protection (IP): EV006405 Ambient class: IEK_V0000010 Number of poles (total): 4 Voltage type: EV000509 Built-in depth: 74,3 Type of electric connection: EV000415 Release actuating time in short-circuit tm zone: 0,1 Nominal rated voltage: 400 Number of poles (TrA inclus) Detalii online: https://www.materialeelectrice.ro/siguranta-automata-va47-100-4p-35a-		
Primary current: 35 ⁻ Release characteristic: EV000084 Nominal operating voltage: 400 Rated short-circuit breaking capacity EN 60898: 10 Width in number of modular spacings: 6 Max. cross section incoming cable: 35 Nominal voltage DC: ≤ 60 Rated surge voltage invariability: 6 Current limiting class: 3 Frequency: 50 Degree of protection (IP): EV006405 Ambient class: IEK_V0000010 Number of poles (total): 4 Voltage type: EV000509 Built-in depth: 74,3 Type of electric connection: EV00415 Release actuating time in short-circuit tm zone: 0,1 Nominal rated current: 35.0 Nominal rated voltage: 400 Number of protected poles: 4 Pret: 0,00 lei (TVA inclus) Detalii online: https://www.materialeelectrice.ro/siguranta-automata-va47-100-4p-35a-		Higher switching capacity of 10000A provides for installing VA47-100 as input circuit
Nominal operating voltage: 400 Rated short-circuit breaking capacity EN 60898: 10 Width in number of modular spacings: 6 Max. cross section incoming cable: 35 Nominal voltage DC: ≤ 60 Rated surge voltage invariability: 6 Current limiting class: 3 Frequency: 50 Frequency: 50 Pegree of protection (IP): EV006405 Ambient class: IEK_V000010 Number of poles (total): 4 Voltage type: EV000509 Built-in depth: 74,3 Type of electric connection: EV000415 Release actuating time in short-circuit tm zone: 0,1 Nominal rated voltage: 400 Number of protected poles: 4 Pret: 0,00 lei (TVA inclus) Detalti online: https://www.materialeelectrice.ro/siguranta-automata-va47-100-4p-35a-		Primary current: 35
Rated short-circuit breaking capacity EN 60898: 10 Width in number of modular spacings: 6 Max. cross section incoming cable: 35 Nominal voltage DC: ≤ 60 Rated surge voltage invariability: 6 Current limiting class: 3 Frequency: 50 Degree of protection (IP): EV006405 Ambient class: IEK_V0000010 Number of poles (total): 4 Voltage type: EV000509 Built-in depth: 74,3 Type of electric connection: EV000415 Release actuating time in short-circuit tm zone: 0,1 Nominal rated current: 35.0 Nominal rated voltage: 400 Number of protected poles: 4 Pret: 0,00 lei (TVA inclus) Detalli online: https://www.materialeelectrice.ro/siguranta-automata-va47-100-4p-35a-		
Width in number of modular spacings: 6 Max. cross section incoming cable: 35 Nominal voltage DC: ≤ 60 Rated surge voltage invariability: 6 Current limiting class: 3 Frequency: 50 Degree of protection (IP): EV006405 Ambient class: IEK_V0000010 Number of poles (total): 4 Voltage type: EV000509 Built-in depth: 74,3 Type of electric connection: EV000415 Release actuating time in short-circuit tm zone: 0,1 Nominal rated voltage: 400 Number of protected poles: 4 Pret: 0,00 lei (TVA inclus) Detalii online: https://www.materialeelectrice.ro/siguranta-automata-va47-100-4p-35a-		
Nominal voltage DC: ≤ 60 Rated surge voltage invariability: 6 Current limiting class: 3 Frequency: 50 Degree of protection (IP): EV006405 Ambient class: IEK_V000010 Number of poles (total): 4 Voltage type: EV000509 Built-in depth: 74,3 Type of electric connection: EV000415 Release actuating time in short-circuit tm zone: 0,1 Nominal rated current: 35.0 Nominal rated voltage: 400 Number of protected poles: 4 Pret: 0,00 lei (TVA inclus) Detalii online: https://www.materialeelectrice.ro/siguranta-automata-va47-100-4p-35a-		Width in number of modular spacings: 6
Rated surge voltage invariability: 6 Current limiting class: 3 Frequency: 50 Degree of protection (IP): EV006405 Ambient class: IEK_V0000010 Number of poles (total): 4 Voltage type: EV000509 Built-in depth: 74,3 Type of electric connection: EV000415 Release actuating time in short-circuit tm zone: 0,1 Nominal rated current: 35.0 Nominal rated voltage: 400 Number of protected poles: 4 Pret: 0,00 lei (TVA inclus) Detalii online: https://www.materialeelectrice.ro/siguranta-automata-va47-100-4p-35a-		
Current limiting class: 3 Frequency: 50 Frequency: 50 Degree of protection (IP): EV006405 Ambient class: IEK_V0000010 Number of poles (total): 4 Voltage type: EV000509 Built-in depth: 74,3 Type of electric connection: EV000415 Release actuating time in short-circuit tm zone: 0,1 Nominal rated current: 35.0 Nominal rated voltage: 400 Number of protected poles: 4 Pret: 0,00 lei (TVA inclus) Detalii online: https://www.materialeelectrice.ro/siguranta-automata-va47-100-4p-35a-		
Frequency: 50 Degree of protection (IP): EV006405 Ambient class: IEK_V0000010 Number of poles (total): 4 Voltage type: EV000509 Built-in depth: 74,3 Type of electric connection: EV000415 Release actuating time in short-circuit tm zone: 0,1 Nominal rated current: 35.0 Nominal rated voltage: 400 Number of protected poles: 4 Pret: 0,00 lei (TVA inclus) Detalii online: https://www.materialeelectrice.ro/siguranta-automata-va47-100-4p-35a-		Current limiting class: 3
Degree of protection (IP): EV006405 Ambient class: IEK_V0000010 Number of poles (total): 4 Voltage type: EV00509 Built-in depth: 74,3 Type of electric connection: EV000415 Release actuating time in short-circuit tm zone: 0,1 Nominal rated current: 35.0 Nominal rated voltage: 400 Number of protected poles: 4 Pret: 0,00 lei (TVA inclus) Detalii online: https://www.materialeelectrice.ro/siguranta-automata-va47-100-4p-35a-		
Ambient class: IEK_V0000010 Number of poles (total): 4 Voltage type: EV000509 Built-in depth: 74,3 Type of electric connection: EV000415 Release actuating time in short-circuit tm zone: 0,1 Nominal rated current: 35.0 Nominal rated voltage: 400 Number of protected poles: 4 Pret: 0,00 lei (TVA inclus) Detalii online: https://www.materialeelectrice.ro/siguranta-automata-va47-100-4p-35a-		Degree of protection (IP): EV006405
Voltage type: EV000509 Built-in depth: 74,3 Type of electric connection: EV000415 Release actuating time in short-circuit tm zone: 0,1 Nominal rated current: 35.0 Nominal rated voltage: 400 Number of protected poles: 4 Pret: 0,00 lei (TVA inclus) Detalii online: https://www.materialeelectrice.ro/siguranta-automata-va47-100-4p-35a-		Ambient class: IEK V0000010
Built-in depth: 74,3 Type of electric connection: EV000415 Release actuating time in short-circuit tm zone: 0,1 Nominal rated current: 35.0 Nominal rated voltage: 400 Number of protected poles: 4 Pret: 0,00 lei (TVA inclus) Detalii online: https://www.materialeelectrice.ro/siguranta-automata-va47-100-4p-35a-		Number of poles (total): 4
Type of electric connection: EV000415 Release actuating time in short-circuit tm zone: 0,1 Nominal rated current: 35.0 Nominal rated voltage: 400 Number of protected poles: 4 Pret: 0,00 lei (TVA inclus) Detalii online: https://www.materialeelectrice.ro/siguranta-automata-va47-100-4p-35a-		Built-in depth: 74.3
Nominal rated current: 35.0 Nominal rated voltage: 400 Number of protected poles: 4 Pret: 0,00 lei (TVA inclus) Detalii online: https://www.materialeelectrice.ro/siguranta-automata-va47-100-4p-35a-		Type of electric connection: EV000415
Nominal rated voltage: 400 Number of protected poles: 4 Pret: 0,00 lei (TVA inclus) Detalii online: https://www.materialeelectrice.ro/siguranta-automata-va47-100-4p-35a-		
Number of protected poles: 4 Pret: 0,00 lei (TVA inclus) Detalii online: https://www.materialeelectrice.ro/siguranta-automata-va47-100-4p-35a-		
Detalii online: https://www.materialeelectrice.ro/siguranta-automata-va47-100-4p-35a-		Number of protected poles: 4
		Pret: 0,00 lei (TVA inclus)
10ka-curba-c-300830		Detalii online: https://www.materialeelectrice.ro/siguranta-automata-va47-100-4p-35a-10ka-curba-c-306830