



Furnizor: **Sc Trivolt Distribution SRL** Reg. com.: J23/3300/2016 CIF: RO36421140 Adresa: Strada Apusului nr 3 (primul sens giratoriu Tehodor Pallady-Autostrada Soarelui), Catelu, Ilfov Banca: BRD IBAN: RO34BRDE441SV13182234410

LEGRAND LAMPA DE EMERGENTA B65 - AUTOTEST/ADDRESS
<u>MAINT./NON MAINT 350 LM - 1H - LED</u>
Caracteristici tehnice Autotest and addressable luminaires - Maintained/Non-maintained (M/NM) Autotest/addressable luminaires incorporate an automatic self-testing system in order to check emergency lighting Tests result is visible on 2 signalling LEDs (green-OK and yellow-defective) Addressable function is activated by setting an ID on each luminaire with configuration tool (Cat.No 0 626 10) and wiring a complementary BUS line Operating state of all addressable luminaires can be centralized by the control interface (Cat.No 0 626 00) and monitored on a local touch screen controller (Cat.No 0 626 01), or with the building's plan on Legrand Vision System (LVS2) PC software Cat.No 0 626 01, or with the building is plan on Legrand Vision System (LVS2) PC software Cat.No 0 626 02 These Maintained luminaires can also operate in Non-maintained mode according to the wiring of normal lighting 350 lm - 1h (LEDs) Caracteristici generale B65 LED - weatherproof self-contained emergency lighting luminaire LED Weatherproof LED maintained and non-maintained units Certified to IEC and EN 60598-2-22 standards High Putere LEDs. IP 65 - IK 07 Plug-in base to ease fixing, cabling and connection Duration: 1 and 3 hours. Ni-Cd or Ni-MH batteries. Recharge time: 24 hours Charge monitor with a green LED. Tensiune de alimentare: 230 V \pm 10%- 50/60 Hz. Class II High-capacity screw terminals (2 x 2.5mm ²) 3 flexible cable entries for O16, 20 and 25 mm tubes Can be equipped with metallic protection grids Cat.Nos 0 626 90/92 Pret: 712,02 lei (TVA inclus) Detalii online: https://www.materialeelectrice.ro/lampa-de-emergenta-b65-autotest- address-maint-non-maint-350-lm-1h-led-225966