

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



LEGRAND INTRERUPATOR GENERAL TIP USOL250 HP S1
ELECTRONIC MCCB CU ELECTRONIC EARTH LEAKAGE MODULE
FIXED VERSION - 36KA - 4P - 250A

Caracteristici tehnice
MCCBs with electronic earth leakage module - fixed version
Protection against overloads:
I_r adjustable from 0.4 to 1 x I_n
t_r adjustable from 3 to 15s
Protection against short circuits:
I_{sd} adjustable from 1.5 to 10 x I_r
t_{sd} adjustable from 0 to 0.5s
Equipped with earth leakage module with knobs
Adjustable sensitivity: 0.03 - 0.3 - 1 - 3 A
Adjustable tripping: 0 - 0.3 - 1 - 3s (with 0.03 A possible only 0s)
Breaking capacity I_{cu} 36 kA (400 V~)
4P
I_n : 250 A
Caracteristici generale
DPX³ 250 HP - S1 electronic release MCCBs from 40 to 250 A - fixing on plate
Moulded case MCCBs for switching, control isolation and protection of low Tensiune
electrical lines
Can be fitted with auxiliaries
Furnizat cu: screws for connection fixing screws, connection plates for bars and cable
lugs and insulated shileds (phase barriers)
Can be fitted with cage terminals 120 mm² max. (flexible cable) or 150 mm² max. rigid
cable
Can be mounted on plate in XL³ and XL³ S cabinets and enclosures
Conform to IEC 60947-2
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/intrerupator-general-tip-usol250-hp-s1-electronic-mccb-cu-electronic-earth-leakage-module-fixed-version-36ka-4p-250a-228817>