

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**LEGRAND INTRERUPATOR GENERAL TIP USOL250 HP THERMAL
MAGNETIC MCCB CU ELECTRONIC EARTH LEAKAGE MODULE FIXED
VERSION - 36KA - 4P - 63A**

Caracteristici tehnice
MCCBs with electronic earth leakage module - fixed version
Thermal adjustable from 0.8 to 1 In
Magnetic:
fixed at 400 A for $I_n \leq 40$ A,
adjustable from 6.5 to 13 In for $I_n = 50$ A,
adjustable from 5 to 10 In for $I_n \geq 63$ A
Equipped with earth leakage module
Adjustable sensitivity: 0.03 - 0.3 - 1 - 3 A
Adjustable tripping: 0 - 0.3 - 1 - 3s (with 0.03 A possible only 0s)
Breaking capacity Icu 36 kA (400 V~)
4P
In : 63 A
Caracteristici generale
DPX³ 250 HP - thermal magnetic release MCCBs from 16 to 250 A - fixing on plate
Moulded case MCCBs for switching, control isolation and protection of low Tensiune
electrical lines
Can be fitted with auxiliaries
Furnizat cu: screws for connections, fixing screws, and insulated shileds (phase barriers)
Can be fitted with cage terminals 120 mm² max. (flexible cable) or 150 mm² max. rigid
cable
Can be mounted on plate in XL³ and XL³ S cabinets and enclosures
Conform to IEC 60947-2
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/intrerupator-general-tip-usol250-hp-thermal-magnetic-mccb-cu-electronic-earth-leakage-module-fixed-version-36ka-4p-63a-228866>