

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



**LEGRAND INTRERUPATOR GENERAL TIP USOL250 HP THERMAL  
MAGNETIC MCCB CU ELECTRONIC EARTH LEAKAGE MODULE FIXED  
VERSION - 50KA - 4P - 50A**

Caracteristici tehnice  
MCCBs with electronic earth leakage module - fixed version  
Thermal adjustable from 0.8 to 1 In  
Magnetic:  
fixed at 400 A for  $I_n \leq 40$  A,  
adjustable from 6.5 to 13 In for  $I_n = 50$  A,  
adjustable from 5 to 10 In for  $I_n \geq 63$  A  
Equipped with earth leakage module  
Adjustable sensitivity: 0.03 - 0.3 - 1 - 3 A  
Adjustable tripping: 0 - 0.3 - 1 - 3s (with 0.03 A possible only 0s)  
Breaking capacity Icu 50 kA (400 V~)  
4P  
In : 50 A  
Caracteristici generale  
DPX<sup>3</sup> 250 HP - thermal magnetic release MCCBs from 16 to 250 A - fixing on plate  
Moulded case MCCBs for switching, control isolation and protection of low Tensiune  
electrical lines  
Can be fitted with auxiliaries  
Furnizat cu: screws for connections, fixing screws, and insulated shileds (phase barriers)  
Can be fitted with cage terminals 120 mm<sup>2</sup> max. (flexible cable) or 150 mm<sup>2</sup> max. rigid  
cable  
Can be mounted on plate in XL<sup>3</sup> and XL<sup>3</sup> S cabinets and enclosures  
Conform to IEC 60947-2  
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialeelectric.ro/intrerupator-general-tip-usol250-hp-thermal-magnetic-mccb-cu-electronic-earth-leakage-module-fixed-version-50ka-4p-50a-228878>