



Furnizor: **Sc Trivolt Distribution SRL** Reg. com.: J23/3300/2016 CIF: RO36421140 Adresa: Strada Apusului nr 3 (primul sens giratoriu Tehodor Pallady-Autostrada Soarelui), Catelu, Ilfov

Banca: BRD

IBAN: RO34BRDE441SV13182234410





Caracteristici tehnice

KNX temperature control panels

Connected directly to BUS/KNX cable (supplied with tap-off connector)

The control unit must be programmed using ETS software Flush mounted 1.6" backlight display with 4 pushbuttons and embedded temperature

probe
Used to manage different types of heating/cooling system (FCU, heating/cooling valve, fan, electric load, ...) in combination through KNX with dedicated HVAC controller:

Monitoring the ambient temperature with desired unit Adjustment of the temperature set-point and/or fan speed Selection of operating mode (comfort, eco, protection, OFF)

To be installed in Montaj incastrat boxes

2 module

Arteor version

To be equipped with Arteor support frames and plates Caracteristici generale

Lighting Management - KNX manual controls
Directly connected to the KNX Bus (supplied with KNX connector)

Programming through ETS software
For lighting control (ON/OFF, dim, scenario, etc.), shutters and slats controls,

automation control

Equipped with 4 to 6 programmable Red Green Blue LEDs (12 colours available) to indicate the status of the loads and provide system and alarm status feedback Pret: 978,36 lei (TVA inclus)

 $\label{lem:decomposition} \textbf{Detalii on line:} \ https://www.materialeelectrice.ro/knx-temperature-controller-montajincastrat-2-module-229460$