

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



LEGRAND DESCARCATOR SPD - T2 - IMAX 40 KA/POLE - 4P

Caracteristici tehnice

T2 SPDs

SPDs with plug-in module and status indicators:

Green: SPD operational

Orange: plug-in module to be replaced

T2 - I_{max} 40 kA/pole

SPDs recommended for Putere installations

Up: 1.7 kV - In: 20 kA/pole - U_c: 320 V~

Earthing systems : TT, TNC, TNS

Recommended MCB: DX³ 25 A - C curve

Numar de poli : 4P

Remote status monitoring (FS contact) : No

Numar de module : 4

Caracteristici generale

Class II (T2) low Tensiune SPDs

Protection against transient overTensiuness for 230/400 V~ Putere networks (50/60 Hz).

SPDs compliant with EN/IEC 61643-11 standards

Recommended for distribution boards

Pret: 434,62 lei (TVA inclus)

Detalii online: <https://www.materialeelectric.ro/descarcator-spd-t2-imax-40-ka-pole-4p-235721>