

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**LEGRAND TUB RIGID PREMUFAT - SHOCK RESISTANCE 2 JOULES -
AA~ EXT. 32 MM**

Caracteristici tehnice
Medium impact rigid conduits with integrated coupling
PVC without Pb, Sn, Cd (RoHS compliant)
Non flame propagating
Surface-mounting or Montaj incastrat
Suitable for prefabricated concrete. Conforming to European standard: EN/IEC 61386-21
Crush resistance: 750 Newtons. Impact resistance: 2 joules at - 5 °C
Min operating t°: - 5 °C ; Max operating t°: + 60 °C
IK 07
Can be used outside
Supplied wrapped in film. Light grey (RAL 7035)
Lungime of tubes: 3 m
O exterior : : 32 mm
O interior : : 27.8 mm
thickness : : 2.10 mm
Caracteristici generale
Rigid conduits
Pret: 11,70 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/tub-rigid-premufat-shock-resistance-2-joules-oe-ext-32-mm-236896>