



Furnizor: **Sc Trivolt Distribution SRL** Reg. com.: J23/3300/2016 CIF: RO36421140 Adresa: Strada Apusului nr 3 (primul sens giratoriu Tehodor Pallady-Autostrada Soarelui), Catelu, Ilfov Banca: BRD IBAN: RO34BRDE441SV13182234410

LEGRAND ZERO-U SINGLE PHASE PDU LCSÂ ³ - 20XC13 + 4XC19 -IEC 60320 STANDARD -PENTRU TERMINAL BLOCK
Caracteristici tehnice PDU Basic IEC 60320 standard 20 C13 outlets + 4 C19 outlets with cord locking system Connection on terminal block up to 6 mm ² Caracteristici generale Legrand cabling system LCS ³ energy Distribution - single-phase Zero-U Basic Putere Distribution Units (PDU) To provide ~ electric Putere for IT equipment in 19" enclosures Single phase Zero-U PDUs for vertical mounting in the cabinet 230 V - 50/60 Hz Tensiune de alimentare PDUs with 2 circuits protected by 16 A uni + neutral MCB in a support with projecting edges to avoid accidental breakdown. Each circuit is identified by color coding. The total number of outlets is distributed equally between the 2 circuits. 2P+E outlets: C13 and C19 standard outlets, French/German/British standards outlets equipped with safety shutters, French/German standards outlets inclined at 55° 330° rotating cable input for a perfect orientation of the cable and no interference in the cabinet C13 and C19 standard outlets are equipped with cord locking system to avoid any accidental disconnection. Universal solution compatible with all the cords (C14 plugs for C13 and C20 plugs for C19) Delivered with 2 sets of metallic mounting brackets: button brackets (for quick fixing and variable pitch) and standard brackets (for screw fixing) Black module (outlets and functions) Aluminium profile Pret: 1 614,44 lei (TVA inclus) Detalii online: https://www.materialeelectrice.ro/zero-u-single-phase-pdu-lcs3-20xc13- 4xc19-iec-60320-standard-pentru-terminal-block-237434