



Furnizor: **Sc Trivolt Distribution SRL** Reg. com.: J23/3300/2016 CIF: RO36421140 Adresa: Strada Apusului nr 3 ( primul sens giratoriu Tehodor Pallady-Autostrada Soarelui), Catelu, Ilfov Banca: BRD IBAN: RO34BRDE441SV13182234410

	LEGRAND ZERO-U THREE PHASE PDU LCSÂ <sup>3</sup> - 18XC13 + 6XC19 - IEC 60320 STANDARD
p	Caracteristici tehnice PDU Basic IEC 60320 standard 18 C13 outlets + 6 C19 outlets with cord locking system 3 m Tensiune de alimentare cord with IEC60309 16 A 3P+N+E plug Caracteristici generale Legrand cabling system LCS <sup>3</sup> energy Distribution - three phase Zero-U Putere Distribution Units To provide ~ electric Putere for IT equipment in 19" enclosures Three phase Zero-U PDUs for vertical mounting in the cabinet 400 V - 50/60 Hz Tensiune de alimentare Each circuit is protected by 16 A single pole MCB in a support with projecting edges to avoid accidental breakdown. 1 circuit per phase, each with 6 IEC 60320 C13 outlets and 2 IEC 60320 C19 outlets 330° rotating cable input for a perfect orientation of the cable and no interference in the cabinet C13 and C19 standard outlets are equipped with cord locking system to avoid any accidental disconnection. Universal solution compatible with all the cords (C14 plugs for C13 and C20 plugs for C19) Delivered with 2 sets of metallic mounting brackets: button brackets (for quick fixing and variable pitch) and standard brackets (for screw fixing) Black module (outlets and functions) Aluminium profile Pret: 1 915,04 lei (TVA inclus) Detalii online: https://www.materialeelectrice.ro/zero-u-three-phase-pdu-lcs3-18xc13- 6xc19-iec-60320-standard-237443