

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



PHILIPS BALASTURI XITANIUM LED    PROGRAMABILE XITANIUM 75W 0.35-0.7A GL PROG SXT

General Information
Flux luminos constant
Programabil
Num  r de produse pe MCB (16 A tip B) (max.)
7
Operating and Electrical
Frecven   de intrare
50 to 60 Hz
Deformare armonic   total   IEC (max.)
20 %
Curent de ie  ire ondulatoriu (nom.)
30 %
Eficien    maxim  
92 %
Factor de putere sarcin   100% (min.)
0,97
Curent de ie  ire (max.)
700 mA
Curent de ie  ire (nom.)
Programmable (350-700) mA
Toleran    curent de ie  ire (max.)
5 %
Toleran    curent de ie  ire (min.)
-5 %
Tensiune de intrare (CA)
120-277 V
Factor de putere sarcin   50% (min.)
0,92
Curent de scurgere la p  mant (max.)
0,7 mA
Curent de intrare (max.)
350 mA
Putere de intrare (nom.)
85 W
Varf curent de pornire (max.)
108 A
Putere de ie  ire (nom.)
30-75 W
Tensiune de ie  ire
80-152 V
L  ime curent de pornire la 50% din varf
140   s
Wiring
Lungime cablu de comand  
500 mm
Lungime cablu ie  ire
500 mm
Sec  iune transversal   cablu de comand   (nom.)
0,82 mm  
Sec  iune transversal   cablu ie  ire (nom.)
0,82 mm  
Sec  iune transversal   cablu de intrare
0,82 mm  
Temperature
T-Ambient (max.)
55   C
T-Ambient (min.)
-40   C
Durat   de via   T-case (nom.)
71   C
Maximum T-case (max.)
80   C
Protec  ie temperatur   modul
Programmable
Comutator oprire cutie T (nom.)
92   C
Controls and Dimming
Interfa   sistem de comand  
1-10V/DALI/Dynadimmer
Interval reglare a intensit  ii luminoase
100-10 %
Timp reglare a intensit  ii luminoase Lumistep
-
Timpul regl  rii intensit  ii luminoase Lumistep dup   miezul nop  ii
-
Mechanical and Housing

Culoare carcasa
Black
Carcasa
F-CAN 240mm
Dimensiuni carcasa
240.5 x 59.8 x 37.6
Approval and Application
Protecie contra supratensiunii (regim comun/diferential)
3/3 kV
Clasificare IP
IP 66
[Ingress Protection 66]
Clasificare izolare
Class II
Matri de omologare
Certificat ENEC
Marcaj CE
Conformitate RoHS
Product Data
Cod complet produs
87182911887900
Nume comand produs
Xitanium 75W 0.35-0.7A Prog GL sXt
EAN/UPC - Produs
8718291999799
Cod de comand
11887900
Numarator SAP - Cantitate per pachet
1
Numarator SAP - Pachete per exterior
10
Material SAP
929000702302
Greutate net SAP (bucata)
1,048 kg
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/balasturi-xitanium-led-programabile-xitanium-75w-0-35-0-7a-gl-prog-sxt-252362>