

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



PHILIPS INTERIOR - HID ELECTRONIC HID-AV C 35-70 /S CDM 220-240V 50/60HZ

General Information
Cod aplicaÈie
-
Tip lampÄf
CDM
NumÄfr de lÄfmpi
1 bucatÄf/unitate
Adecvat pentru uz la exterior
No
NumÄfr de produse pe MCB (16 A tip B) (nom.)
58
Repornire automatÄf
Yes
Operating and Electrical
Tensiune de intrare
220 to 240 V
FrecvenÈÄf de intrare
De la 50 panÄf la 60 Hz
Tensiune minimÄf de lucru reÈea (min.)
198 V
Factor de putere sarcinÄf 100% (nom.)
0,95
Tensiune aprindere (max.)
5,0 kV
Tensiune aprindere (min.)
3,0 kV
Timp de stingere aprindere (nom.)
19 min
PerformanÈÄf tensiune reÈea (CA)
198-254V
SiguranÈÄf tensiune reÈea (CA)
180-264V
Curent de scurgere la pÄfmant (max.)
0,25 mA
LÄfÈime curent de pornire
10 ms
ToleranÈÄa puterii lÄfmpii
-3%/+3%
Varf curent de pornire (max.)
8 A
Wiring
Capacitate cabluri ieÈ™ire - reciproc (nom.)
160 pF
Lungime cablu de la dispozitiv la lampÄf
2 m
Lungime bandÄf cabluri
10.0-11.0 mm
SecÈiune transversalÄf cablu contact balast
0.75-2.50 mm²
Tip conector
WAGO series 804
System characteristics
Putere nominalÄf lampÄf-balast
35-70 W
Putere lampÄf pe CDM
39-73 W
Pierdere de putere pe CDM
5-7 W
Temperature
T-Ambient (max.)
55 °C
T-Ambient (min.)
-20 °C
T-Storage (max.)
80 °C
T-Storage (min.)
-25 °C
DuratÄf de viaÈÄf T-case (nom.)
80 °C
Controls and Dimming
InterfaÈÄf sistem de comandÄf
-
Mechanical and Housing
CarcasÄf
/S
Approval and Application

Protecie contra supratensiunii (regim comun/diferenial)
EN61547 (L-L 2kV, L-G 4kV) kV
Clasificare IP corp de iluminat
Not Specified
Protecie la supratensiune 400 V c.a.
5 min
Protecie activ la temperatur
Yes
EMI 9 kHz ... 300 MHz
CISPR 15 ed 7.2
Standard de siguran
EN 61347-2-12 and 2-1
Standard de calitate
ISO 9000:2000
Standard de mediu
ISO 14001
Standard emisii de curent armonic
IEC 61000-3-2
Standard vibraii
IEC68-2-6 F c
Standard protecii
IEC 68-2-29 Eb
Standard umiditate
IEC 60928 clause 13
Mrci de omologare
Marcaj F
Marcaj CE
Certificat ENEC
Certificat VDE
Certificat CB
VDE-EMC marking
Nivel de zgomot ETMi de zgomot
20 dB(A)
Product Data
Cod complet produs
871829123310700
Nume comand produs
HID-AV C 35-70 /S CDM 220-240V 50/60Hz
EAN/UPC - Produs
8718291233107
Cod de comand
23310700
Numrtor SAP - Cantitate per pachet
1
Numrtor SAP - Pachete per exterior
12
Material SAP
913700683866
Greutate net SAP (bucat)
0,220 kg
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/interior-hid-electronic-hid-av-c-35-70-s-cdm-220-240v-50-60hz-252371>