

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



PHILIPS HID ELECTROMAGNETIC BSN 50 K302-A2-ITS 230V 50HZ

General Information

Cod aplicaÈie

K302-A2-ITS

Design

BC1-118

Tip lampÄf

SON/CDO

NumÄfr de lÄfmpi

1 bucatÄf/unitate

Operating and Electrical

Tensiune de intrare

230 V

FrecvenÈÄf de intrare

50 Hz

Factor de putere sarcinÄf 100% (nom.)

0,85

PerformanÈÄf tensiune reÈea (CA)

-8%+6%

SiguranÈÄf tensiune reÈea (CA)

-10%+10%

Curent de intrare cu corecÈie PF

0.35 A

Curent de intrare fÄfrÄf corecÈie PF

0.76 A

Factor de putere fÄfrÄf compensare PF (nom.)

0,35

Pierderi de putere (nom.)

8.3 W

Wiring

Lungime bandÄf cabluri

6.0 mm

SecÈiune transversalÄf cablu contact balast

2.5 mm²

Tip conector

Screw

System characteristics

Condensator

10µF/250V

Putere nominalÄf lampÄf-balast

50 W

Ignitor recomandat

for SON/CDO/CDM lamps ignitor SKD 578 (913700655366) or series digital SUD40

(913700193591) only CDM

Temperature

T-Storage (max.)

130 °C

T-Storage (min.)

-30 °C

Bobinaj T (max.)

140 °C

CondiÈii normale Delta-T

50 °C

Approval and Application

ProtecÈie activÄf la temperaturÄf

Yes

MÄfrci de omologare

Marcaj CE

Certificat ENEC

Product Data

Cod complet produs

871869674078100

Nume comandÄf produs

BSN 50 K302-A2-ITS 230V 50Hz

EAN/UPC - Produs

8718696740781

Cod de comandÄf

74078100

NumÄfrÄftor SAP - Cantitate per pachet

1

NumÄfrÄftor SAP - Pachete per exterior

6

Material SAP

913700751926

Greutate netÄf SAP (bucatÄf)

1,260 kg

Pret: 0,00 lei (TVA inclus)

