

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



PHILIPS HID ELECTROMAGNETIC BHL 250 K307 230/240V 50HZ **BC2-134**

General Information

Cod aplicaÈie

K307-A2

Design

BC2-134

Tip lampÄf

HPL/HPI

NumÄfr de lÄfmpi

1 bucatÄf/unitate

Operating and Electrical

Tensiune de intrare

230 V (default) or 240 V

FrecvenÈÄf de intrare

50 Hz

Factor de putere sarcinÄf 100% (nom.)

0,85

PerformanÈÄf tensiune reÈea (CA)

-8%+6%

SiguranÈÄf tensiune reÈea (CA)

-10%+10%

Curent de intrare cu corecÈie PF

1.40 A

Curent de intrare fÄfrÄf corecÈie PF

2.13 A

Factor de putere fÄfrÄf compensare PF (nom.)

0,55

Pierderi de putere (nom.)

18.5/19.4 W

Wiring

Lungime bandÄf cabluri

7.0 mm

SecÈiune transversalÄf cablu contact balast

1.00-2.50 mm²

Tip conector

Screw

System characteristics

Condensator

18µF/250V

Putere nominalÄf lampÄf-balast

250 W

Ignitor recomandat

no ignitor for HPL-N for HPI-T ignitor SI51 (913619519966)

Temperature

T-Storage (max.)

130 °C

T-Storage (min.)

-30 °C

Bobinaj T (max.)

130 °C

CondiÈii normale Delta-T

80/85 °C

Approval and Application

MÄfrci de omologare

Marcaj CE

Certificat ENEC

Product Data

Cod complet produs

872790088701300

Nume comandÄf produs

BHL 250 K307-A2 230/240V 50Hz BC2-134

EAN/UPC - Produs

8711500881588

Cod de comandÄf

88701300

NumÄfrÄftor SAP - Cantitate per pachet

1

NumÄfrÄftor SAP - Pachete per exterior

6

Material SAP

913700278026

Greutate netÄf SAP (bucatÄf)

2,245 kg

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/hid-electromagnetic-bhl-250-k307-230-240v-50hz-bc2-134-252421>

