

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



PHILIPS HID ELECTROMAGNETIC BHL 400 L40 230V 50HZ HD2-151

General Information

Cod aplicaÈie

L40-A2

Design

HD2-151

Tip lampÄf

HPL/HPI

NumÄfr de lÄfmpi

1 bucatÄf/unitate

Operating and Electrical

Tensiune de intrare

230 V

FrecvenÈÄf de intrare

50 Hz

Factor de putere sarcinÄf 100% (nom.)

0,87

PerformanÈÄf tensiune reÈea (CA)

-8%+6%

SiguranÈÄf tensiune reÈea (CA)

-10%+10%

Curent de intrare cu corecÈie PF

2.15 A

Curent de intrare fÄfrÄf corecÈie PF

3.25 A

Factor de putere fÄfrÄf compensare PF (nom.)

0,55

Pierderi de putere (nom.)

22.0 W

Wiring

Lungime bandÄf cabluri

7.0 mm

SecÈiune transversalÄf cablu contact balast

0.70-6.00 mm²

Tip conector

Screw

System characteristics

Putere nominalÄf lampÄf-balast

400 W

Ignitor recomandat

no ignitor for HPL-N for HPI-T ignitor SI51 (913619519966)

Temperature

T-Storage (max.)

130 °C

T-Storage (min.)

-30 °C

Bobinaj T (max.)

130 °C

CondiÈii normale Delta-T

80 °C

Approval and Application

MÄfrci de omologare

Marcaj CE

Certificat ENEC

Product Data

Cod complet produs

871150091953330

Nume comandÄf produs

BHL 400 L40-A2 230V 50Hz HD2-151

EAN/UPC - Produs

8711500919533

Cod de comandÄf

91953330

NumÄfrÄftor SAP - Cantitate per pachet

1

NumÄfrÄftor SAP - Pachete per exterior

6

Material SAP

913604920426

Greutate netÄf SAP (bucatÄf)

2,750 kg

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/hid-electromagnetic-bhl-400-l40-230v-50hz-hd2-151-252424>