

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



PHILIPS HID ELECTROMAGNETIC BSN 1000 L78 230/240V 50HZ HP-257

General Information

Cod aplicaÈie

L78-A2

Design

HP-257

Tip lampÄf

SON

NumÄfr de lÄfmpi

1 bucatÄf/unitate

Operating and Electrical

Tensiune de intrare

230 V (default) or 240 V

FrecvenÈÄf de intrare

50 Hz

Tensiune de intrare (clapete multiple)

230/240

Factor de putere sarcinÄf 100% (nom.)

0,87

PerformanÈÄf tensiune reÈea (CA)

-8%+6%

SiguranÈÄf tensiune reÈea (CA)

-10%+10%

Curent de intrare cu corecÈie PF

5.40 A

Curent de intrare fÄfrÄf corecÈie PF

10.30 A

Factor de putere fÄfrÄf compensare PF (nom.)

0,50

Pierderi de putere (nom.)

54.0 W

Wiring

Lungime bandÄf cabluri

7.0 mm

SecÈiune transversalÄf cablu contact balast

0.70-6.00 mm²

Tip conector

Screw

System characteristics

Condensator

100µF/250V

Putere nominalÄf lampÄf-balast

1000 W

Ignitor recomandat

Series ignitor - SN 56 (913619669966) / SN 59 (913619659966)

Temperature

T-Storage (max.)

80 °C

T-Storage (min.)

-25 °C

Bobinaj T (max.)

130 °C

CondiÈii normale Delta-T

70 °C

Approval and Application

MÄfrci de omologare

Marcaj CE

Certificat ENEC

Product Data

Cod complet produs

871150006236900

Nume comandÄf produs

BSN 1000 L78-A2 230/240V 50Hz HP-257

EAN/UPC - Produs

8711500996640

Cod de comandÄf

06236900

NumÄfrÄftor SAP - Cantitate per pachet

1

NumÄfrÄftor SAP - Pachete per exterior

1

Material SAP

913700217503

Greutate netÄf SAP (bucatÄf)

12,700 kg

Pret: 0,00 lei (TVA inclus)

