

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



PHILIPS IGNITORI SKD 578-S 220-240V 50/60HZ

General Information
Cod aplicaÈie
578-S
Tip lampÄf
SON/CDM/MH/HPI/HPA/CDO
NumÄfr de lÄfmpi
1 bucatÄf/unitate
Operating and Electrical
Tensiune de intrare
220 to 240 V
FrecvenÈÄf de intrare
De la 50 panÄf la 60 Hz
Tip aprindere
Semi-Parallel
IncercÄfri aprindere
3
NumÄfr impulsuri de aprindere
1
Timp de aprindere (max.)
1185 s
Tensiune aprindere (max.)
5,00 kV
Tensiune aprindere (min.)
1,80 kV
Tensiune de räfspuns
190 V
PerformanÈÄf tensiune reÈea (CA)
-8%+6%
SiguranÈÄf tensiune reÈea (CA)
-10%+10%
Pierderi de putere (nom.)
0.5 W
Wiring
Lungime bandÄf cabluri
6.0 mm
SecÈiune transversalÄf cablu contact balast
0.50-2.50 mm²
Tip conector
Screw
System characteristics
Putere nominalÄf lampÄf-balast
35-600 W
Temperature
T-Ambient (max.)
85 °C
T-Ambient (min.)
-30 °C
T-Storage (max.)
85 °C
T-Storage (min.)
-35 °C
Maximum T-case (max.)
90 °C
Approval and Application
MÄfrci de omologare
Marcaj CE
Certificat ENEC
Product Data
Cod complet produs
872790089569800
Nume comandÄf produs
SKD 578-S 220-240V 50/60Hz
EAN/UPC - Produs
8711500881779
Cod de comandÄf
89569800
NumÄfrÄftor SAP - Cantitate per pachet
1
NumÄfrÄftor SAP - Pachete per exterior
20
Material SAP
913700655466
Greutate netÄf SAP (bucatÄf)
31,400 g

Pret: 18,03 lei (TVA inclus)

