

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



### **SCHNEIDER BUTON DUBLU, NEW UNICA, 1-POLE 1-WAY, 10AX, 2 MODULE, TERMINAL FARA SURUBURI, NETRATAT, IP4X, ALB**

Schneider Electric New Unica switch NU521118 is a mechanism with zamak fixing frame in color white with 2 rockers. This is a double 1-way switch. The device's fixing mode is screws or claws. Its rated current is 10AX. It is 74.5 mm in width, 74.5 mm in height 34.25 mm in depth with an embedding depth of 21.15 mm. The surface finish is glossy, delivering an elegant and high-end feeling to a room. The IP rating of this device is IP21D which is very high. This switch has screwless terminals connection terminals. Being made of Cu.Zn15, Cu.Zn37, PBT (polybutylene terephthalate) GF31, PC (polycarbonate) GF10 FR, thermoplastic ABS-UV stabilized, zamak material, this switch is quite reliable and resistant. This switch is AENOR, CE, EAC, NF certified. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range of product - New Unica  
Product or component type - Switch  
device presentation - Mechanism with fixing frame  
Technology type - Electromechanical  
Switch function - 1-pole 1-way  
Number of rocker - 2  
Device application - Light control  
Provided equipment - Fixing frame  
Colour tint - White (RAL 9003)  
Type of packing - Flow-pack  
Complementary  
Rated current - 10 AX  
[Ue] rated operational voltage - 250 V  
Network type - AC  
Network frequency - 50/60 Hz  
Electrical durability - 20000 cycles, cos phi = 0.6  
Insulation resistance - > 5 MOhm at 500 V  
Dielectric strength - 2000 V  
Minimum load breaking capacity - 200 operations 1.25 In and 1.1 Un, cos phi = 0.3  
Opening distance - > 3 mm  
Actuator - Rocker  
Number of modules - 2 modules  
Connections - terminals - Screwless terminals  
Cable cross section - 0.5-2.5 mm<sup>2</sup> rigid cable  
0.5-2.5 mm<sup>2</sup> flexible cable  
Material - PBT (polybutylene terephthalate) GF31: release button  
CuZn15: internal link  
Zamak: fixing frame  
Thermoplastic ABS-UV stabilised: mechanism rocker  
PC (polycarbonate) GF10 FR: casing  
CuZn37: terminals  
Marking - Without marking  
Surface finish - Glossy  
specific treatment - integrated within the material - Untreated  
Fixing mode - Screws or claws  
Width - 74.5 mm  
Height - 74.5 mm  
Depth - 34.25 mm  
Embedding depth - 21.15 mm  
Net weight - 0.0639 kg  
Ambient air temperature for operation - -5 to +40 A°C  
Ambient air temperature for storage - -5 to +50 A°C  
Standards - IEC 60669-1  
LV directive  
Product certifications - CE  
AENOR  
EAC  
NF  
VDE  
Resistance to chemical agents - Resistant to alcohol (70 %)  
Resistant to alcohol (96 %)  
Resistant to A-Lactic Acid  
Resistant to diluted quaternary ammonium  
Resistant to diluted bleach  
Resistant to diluted ammonia  
Resistant to soapy water  
Resistant to crystal cleaner  
Resistant to hydrogen peroxide 10 volumes  
Resistant to hexane  
Environment  
IP degree of protection - IP4X  
IK degree of protection - IK04  
Environmental characteristic - Oil

UV resistant  
Acetone  
Liquid soap  
Window-cleaning fluid  
Petrol  
Alcohol  
Bleach  
Packing Units  
Unit Type of Package 1 - PCE  
Number of Units in Package 1 - 1  
Package 1 Height - 4.0 cm  
Package 1 Width - 7.5 cm  
Package 1 Length - 7.5 cm  
Package 1 Weight - 64.0 g  
Unit Type of Package 2 - BB1  
Number of Units in Package 2 - 10  
Package 2 Height - 8.0 cm  
Package 2 Width - 20.0 cm  
Package 2 Length - 22.5 cm  
Package 2 Weight - 740.0 g  
Unit Type of Package 3 - S04  
Number of Units in Package 3 - 120  
Package 3 Height - 30.0 cm  
Package 3 Width - 40.0 cm  
Package 3 Length - 60.0 cm  
Package 3 Weight - 9.539 kg  
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/buton-dublu-new-unica-1-pole-1-way-10ax-2-module-terminal-fara-suruburi-netratat-ip4x-alb-319040>