

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<u>LAPP CABLU DATE JOASA FRECVENTAUNITRONIC LIHCH (TP)</u> <u>2X2X0,5</u> Cabluri pentru transfer de date ecranate, fÄfrÄf halogen, codul de culori conform DIN 47100 È™i perechi torsadate UNITRONIC® LIHCH (TP): Cablu ecranat de date de joasÄf frecvenÄfÄf, fÄfrÄf halogeni, cu perechi torsadate, flexibil (liÈ›e fine 0,34 mm² pentru Maxi TERMIN-POINT®), conductori coloraÄfi conform DIN 47100, capacitate redusÄf, cu densitate redusÄf a fumului TP = perechi torsadate Regulamentul privind Produsele pentru ConstrucÈ›ii (CPR): O selecÈ›ie a numerelor articolelor este disponibilÄf la adresa de Internet www.lappkabel.de/cpr InformaÈ›ii articol Articol nr.: 0038602 NumÄfrul de conductori Äfi secÄfiunea acestora mm²: 2 x 2 x 0.5 Diametru exterior [mm]: 8.1 Index Cupru (kg/km): 48.1 Greutate (kg / km): 93 informaÈ›ii despre produs (PDF) FiÈ™Äf tehnicÄf DeclaraÈ›ie de performanÈ›Äf Beneficii fÄfrÄf halogen: pentru a proteja oamenii È™i obiectele de valoare in caz de incendiu, densitate scazutÄf de fum È™i cantitate micÄf de gaze corozive Decuplarea circuitelor prin torsadarea perechilor (crosstalk effects) Tresa colectivÄf minimizeazÄf interferenÈ›ele electromagnetice Capacitate scÄfzutÄf datoritÄf izolaÄfiei din poliolefinÄf Domeniu de utilizare Pentru utilizare in clÄfdiri publice, sisteme de transport È™i zone industriale Potrivit pentru aplicaÄfii in zone cu aglomerÄfri umane Äfi valori materiale mari care trebuie protejate in caz de incendiu Pentru prelucrarea datelor, masurÄf È™i control, sisteme de siguranÈ›Äf precum È™i cabluri de electronicÄf Pentru utilizare in sisteme de calcul, instrumentaÈ›ie, echipamente de birou - peste tot unde sunt necesare cablurile ecranate, fÄfrÄf halogen È™i cu diametru exterior redus. Caracteristicile produsului Intarzierea propagÄfriei focului: IEC 60332-1-2 fÄfrÄf halogen, conform IEC 60754-1, coroziune redusÄf/ aciditatea gazelor de ardere conform IEC 60754-2, toxicitate redusÄf a gazelor de ardere, conform EN 50305 LSZH (Low smoke zero halogen) Densitate redusÄf a fumului conform IEC 61034-2 Descrierea produsului Conductor din liÄfe fine de cupru neacoperit IzolaÈ›ia conductorului realizatÄf din compus special fÄfrÄf halogen StructurÄf TP Ecran Äfesut din liÄfe de cupru cositorit IzolaÈ›ie exterioarÄf fÄfcutÄf din compus special fÄfrÄf halogen Culoarea izolaÈ›iei exterioare: gri pietriÈ™ (RAL 7032) Norme de referinÈ›Äf / aprobÄfri Bazat pe VDE 0812 ConstrucÈ›ie Pret: 25,02 lei (TVA inclus) Detalii online: https://www.materialeelectrice.ro/cablu-date-joasa-frecventaunitronic-lihch-tp-2x2x0-5-286356
--	---