

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



GEWISS PROIECTOR LED TIP SMART [PRO] 2.0 - 3X2 MODULE -C3
CIRCULAR - 3000K CRI>70 - IP66 - CLASS I

GENERAL INFORMATION - -
OPTIC AND ILLUMINATING FEATURES - -
Context - Sport, Big Areas
Optic - C3 - Circular 20°
Luminaire - LED luminaire with mid and high lumen power
Unified Glare Rating - G*6 - ULOR = 0
Aplicatie - Intern / Extern
Luminanta (lm) - 114500
Unique digital code (Datamatrix) - Currently not present
Efficiency
(lm/W) - 118
Culoare - Gri grafit
Culoare Temperatur - 3000 K
Tip sursă de lumină - LED - Neînlocuibil
Color Rendering Index - CRI>70
Puterea sistemului - 970 W
Standard Deviation Colour Matching - SDCM = 5
LED Lifetime - L90B10(Tq25°C)=40.000h; L80B10(Tq25°C)=90.000h
Photobiological Risk Class - -
Greutate (Kg) - 29
Standard - EN60598-1; EN60598-2-5; IEC 62778; IEC 62471; EN13201
Garanție - 5 ani
ELECTRICAL AND LIGHTING FEATURES - -
Temperatură de stocare - -
Tensiune de alimentare - -
Operating temperature - -30 +50 °C
Frecvență nominală (Hz) - -
MATERIALS - -
Driver - To be ordered separately
Body - Aluminiu turnat
Driver failure rate - See external supply unit
Ecran - Flat tempered glass 4mm
Overvoltage protection - See external supply unit
Optic - Polished quartz and metallized PC HT reflector
Control System - See external supply unit
Gasket - Anti-aging silicone
INSTALLATION AND MAINTENANCE - -
Locking Hook - Hexagonal metric screws
Mounting and installation - High-mast lighting - Wall mounting - Ground mounting
External screw - Stainless steel
Tilt - Rotation on bracket with integrated goniometer
Colour - Polyester powder coated
Wiring - Watertight connector
STANDARDS AND APPROVALS - -
Prindere - Consolă
Clasificare - -
Optic Maintenance - Not available
Dispozitiv cu temperatură la suprafață redusă - Nu
LED Maintenance - Da
Certificare DIN 18032-3 - -
Driver Box - Exterior
IPEA - -
Suprafață maximă expusă la vant - 0,333 m2
Clasă izolație - I
- - -
Clasă de protecție IP - IP66
- - -
Cod IK - IK08
- - -
Glow Test conductori - -
- - -
Ware number - 94054010
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/proiector-led-tip-smart-pro-2-0-3x2-module-c3-circular-3000k-cri-70-ip66-class-i-215650>