



Furnizor: **Sc Trivolt Distribution SRL** Reg. com.: J23/3300/2016 CIF: RO36421140 Adresa: Strada Apusului nr 3 (primul sens giratoriu Tehodor Pallady-Autostrada Soarelui), Catelu, Ilfov Banca: BRD IBAN: RO34BRDE441SV13182234410

IEK ARMAT SIGURANTA AUTOMATA M06N 4P C 10A ARMAT M06N series circuit breakers are designed to protect circuits against overload 0, and short-circuit. The range includes devices with trip characteristics B, C, D and rated currents from 0.5 to 63 A. The rated breaking capacity of ARMAT M06N series circuit breaking capacity waries depending on the rating from 10 10

and curr brea to 50 Poss Lato Tigh Labe Fully Rate Limi Prim Rele Widt Max Rate Curr brea So Poss Lato Tigh Labe Fully Rate Limi Prim Rele Nom Rate Widt Max Rate Curr Poss So So So So So So So So So So So So So	MAT MO6N series circuit breakers are designed to protect circuits against overload short-circuit. The range includes devices with trip characteristics B, C, D and rated ents from 0.5 to 63 A. The rated breaking capacity of ARMAT M06N series circuit kers is 6 kA. The ultimate breaking capacity varies depending on the rating from 10 0 kA.High switching life of 10 000 electrical cycles. sibility to connect FORK busbars on either side of the circuit breaker. h on the dinrail with 2 fixed positions. tening torque up to 5 Nm. al area with transparent cover. y compliant with ROHS directive. a speed tripping device, current limit class 3. ded breaking capacity 6 kA. tt switching capacity from 10 to 50 kA (depending on rating).Number of poles: 4 tary current: 10 asse characteristic: EV00084 inial operating voltage: 400 ed short-circuit breaking capacity EN 60898: 6 th in number of modular spacings: 4 . cross section incoming cable: 25 ed surge voltage invariability: 6 reent limiting class: 3 upency: 50 puency: 50 asse actuating time in short-circuit thr zone: 0,1 ration mode: IEX 0000415 asse actuating time in short-circuit thm zone: 0,1 ration mode: IEX 0000273 ntainalability: EV000404 tianal rated voltage: 400 de lectric connection: EV000415 asse actuating time in short-circuit thm zone: 0,1 ration mode: IEX 0000273 ntainalability: EV000494 tianal rated voltage: 400 de lectric voltage: 400 de lectric voltage: 400 de linal rated voltag
---	--