

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



### **IEK SIGURANTA AUTOMATA VA47-60M 1P 32A 6KA B**

Modular circuit breakers (MCB) VA47-60M designed for automatic disconnection of electrical installations at overcurrent, and operational control of the sectors of electrical circuits. The devices are ideal for use in group boards (for apartment and floor) as well as in the accounting and distribution boards of administrative and residential buildings. Two types of overcurrent protection - thermal and electromagnetic.

Wide handle for easy on/off of the circuit breaker.

DIN rail latch with double fixed position.

Notches on the contact clamps reduce heat loss and increase the mechanical strength of the joint.

Wide operating temperature range from -40°C to +50°C. Number of poles: 1

Primary current: 32

Release characteristic: EV000074

Nominal operating voltage: 230/400

Rated short-circuit breaking capacity EN 60898: 6

Width in number of modular spacings: 1

Max. cross section incoming cable: 25

Current limiting class: 3

Frequency: 50

Frequency: 50

Degree of protection (IP): EV006405

Ambient class: IEK\_V0000010

Mechanical wear resistance:  $\geq 20000$

Electric wear resistance:  $\geq 8000$

Weight of one pole:  $\leq 0,2$

Number of poles (total): 1

Voltage type: EV000509

Built-in depth: 71

Type of electric connection: EV000415

Release actuating time in short-circuit tm zone: 0,1

Nominal rated current: 32.0

Nominal rated voltage: 230

Number of protected poles: 1

Electric shock protection class: EV000601

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialeelectric.ro/siguranta-automata-va47-60m-1p-32a-6ka-b-306597>