



Furnizor: **Sc Trivolt Distribution SRL** Reg. com.: J23/3300/2016 CIF: RO36421140 Adresa: Strada Apusului nr 3 ( primul sens giratoriu Tehodor Pallady-Autostrada Soarelui), Catelu, Ilfov Banca: BRD IBAN: RO34BRDE441SV13182234410

the state	<u>IEK SIGURANTA AUTOMATA VA47-100 1P 32A 10KA CURBA C</u>
1	Modular circuit breakers (MCB) VA47-100 protect distribution and group circuits with active and inductive loads. Recommended for use in lead-in distributors of domestic and industrial electric installations. Two types of protection against overload and short circuit.
I iek	Complete set of supplementary devices with the possibility of simple independent
BA47-100	installation:
C32 230/400 V~ 2	- State contact KS47; - State contact KSV47;
Times 4	- Undervoltage trip RMM47;
	– Low-voltage release RN47. Indication of contact position.
	Latching on DIN-rail with double locking.
1	Wide operating temperature range from -40 to +50° Đ <sub>i</sub> . Updated wider engagement lever with improved contact area.
2	Notches on contact terminals reduce heat loss and increase mechanical stability of the
	connection. Higher switching capacity of 10000A provides for installing VA47-100 as input circuit
	breakers.Number of poles: 1
	Primary current: 32
	Release characteristic: EV000084 Nominal operating voltage: 230/400
	Rated short-circuit breaking capacity EN 60898: 10
	Width in number of modular spacings: 1,5 Max. cross section incoming cable: 35
	Nominal voltage DC: $\leq 60$
	Rated surge voltage invariability: 6 Current limiting class: 3
	Frequency: 50
	Frequency: 50 Degree of protection (IP): EV006405
	Ambient class: IEK V0000010
	Number of poles (total): 1
	Voltage type: EV000509 Built-in depth: 74,3
	Type of electric connection: EV000415
	Release actuating time in short-circuit tm zone: 0,1 Nominal rated current: 32.0
	Nominal rated voltage: 400
	Number of protected poles: 1 Pret: 41,50 lei (TVA inclus)
	Detalii online: https://www.materialeelectrice.ro/siguranta-automata-va47-100-1p-32a-10ka-curba-c-306763