



Furnizor: **Sc Trivolt Distribution SRL** Reg. com.: J23/3300/2016 CIF: RO36421140 Adresa: Strada Apusului nr 3 ( primul sens giratoriu Tehodor Pallady-Autostrada Soarelui), Catelu, Ilfov Banca: BRD IBAN: RO34BRDE441SV13182234410

	IEK SIGURANTA AUTOMATA VA47-100 3P 80A 10KA CURBA D
a a a	
	Modular circuit breakers (MCB) VA47-100 protect distribution and group circuits with
	active and inductive loads. Recommended for use in lead-in distributors of domestic and
	industrial electric installations. Two types of protection against overload and short
	circuit.
	Complete set of supplementary devices with the possibility of simple independent
IEK	installation:
BAA7-100 1979-09	- State contact KS47:
D80	- State contact KSV47;
	- Undervoltage trip RMM47;
	- Low-voltage release RN47.
	Indication of contact position.
	Latching on DIN-rail with double locking.
	Wide operating temperature range from $-40$ to $+50^{\circ}$ $\text{D}_{i}$ .
	Updated wider engagement lever with improved contact area.
	Notches on contact terminals reduce heat loss and increase mechanical stability of the
	connection.
	Higher switching capacity of 10000A provides for installing VA47-100 as input circuit
	breakers.Number of poles: 3
	Primary current: 80
	Release characteristic: EV000413
	Nominal operating voltage: 400
	Rated short-circuit breaking capacity EN 60898: 10
	Width in number of modular spacings: 4,5
	Max. cross section incoming cable: 35
	Nominal voltage DC: $\leq 60$
	Rated surge voltage invariability: 6
	Current limiting class: 3
	Frequency: 50
	Frequency: 50
	Degree of protection (IP): EV006405
	Ambient class: IEK V0000010
	Number of poles (total): 3
	Voltage type: EV000509
	Built-in depth: 74,3
	Type of electric connection: EV000415
	Release actuating time in short-circuit tm zone: 0,1
	Nominal rated current: 80.0
	Nominal rated voltage: 400
	Number of protected poles: 3
	Pret: 0,00 lei (TVA inclus)
	Detalii online: https://www.materialeelectrice.ro/siguranta-automata-va47-100-3p-80a-
	10ka-curba-d-306817