



Furnizor: **Sc Trivolt Distribution SRL** Reg. com.: J23/3300/2016 CIF: RO36421140 Adresa: Strada Apusului nr 3 (primul sens giratoriu Tehodor Pallady-Autostrada Soarelui), Catelu, Ilfov Banca: BRD IBAN: RO34BRDE441SV13182234410

	IEK SIGURANTA AUTOMATA VA47-100 4P 40A 10KA CURBA D
	IEK SIGURANTA AUTOMATA VA47-100 4P 40A 10KA CURBA D Modular circuit breakers (MCB) VA47-100 protect distribution and group circuits with active and inductive loads. Recommended for use in lead-in distributors of domestic and industrial electric installations. Two types of protection against overload and short circuit. Complete set of supplementary devices with the possibility of simple independent installation: - State contact KS47; - State contact KSV47; - Undervoltage trip RMM47; - Low-voltage release RN47. Indication of contact position. Latching on DIN-rail with double locking. Wide operating temperature range from -40 to +50° Đj. Updated wider engagement lever with improved contact area. Notches on contact terminals reduce heat loss and increase mechanical stability of the connection. Higher switching capacity of 10000A provides for installing VA47-100 as input circuit breakers.Number of poles: 4 Primary current: 40 Release characteristic: EV000413 Nominal operating voltage: 400 Rated short-circuit breaking capacity EN 60898: 10 Width in number of modular spacings: 6 Max. cross section incoming cable: 35 Nominal voltage DC: ≤ 60 Rated surge voltage invariability: 6 Current limiting class: 3 Frequency: 50 Frequency: 50
	industrial electric installations. Two types of protection against overload and short
	Complete set of supplementary devices with the possibility of simple independent
1111 - UNIT	- State contact KS47;
1 Provention of the second states of the second sta	- Low-voltage release RN47.
	Indication of contact position.
	Undated wider engagement lever with improved contact area.
	Notches on contact terminals reduce heat loss and increase mechanical stability of the
	Higher switching capacity of 10000A provides for installing VA47-100 as input circuit
	Nominal operating voltage: 400
	Rated short-circuit breaking capacity EN 60898: 10
	Frequency: 50
	Frequency: 50
	Degree of protection (IP): EV006405 Ambient class: IEK V0000010
	Number of poles (total): 4
	Voltage type: EV000509
	Built-in depth: 74,3
	Type of electric connection: EV000415
	Release actuating time in short-circuit tm zone: 0,1
	Nominal rated current: 40.0 Nominal rated voltage: 400
	Number of protected poles: 4
	Pret: 0,00 lei (TVA inclus)
	Detalii online: https://www.materialeelectrice.ro/siguranta-automata-va47-100-4p-40a-10ka-curba-d-306832