



Furnizor: **Sc Trivolt Distribution SRL** Reg. com.: J23/3300/2016 CIF: RO36421140

Adresa: Strada Apusului nr 3 (primul sens giratoriu Tehodor Pallady-Autostrada Soarelui), Catelu, Ilfov

Banca: BRD

IBAN: RO34BRDE441SV13182234410



IEK BIPOLARA CU PROTECTIE DIFERENTIALA RCCB VD1-63S 4P 50A 300MA

Residual Current Circuit Breaker (RCCB) VD1-63S circuit breakers with release mechanism controlled by differential current, without built-in protection against overcurrents, without functional dependence on mains voltage, for household or similar use, with delayed tripping are intended for automatic power cut-off when differential leakage currents occur in single-phase and three-phase AC electric systems of rated voltage up to 400 V. VD1-63S are designed for installation in low-voltage complex input and distribution devices used in residential, public and industrial objects as well as construction sites. Electromechanical design, with delayed tripping.

The most reliable protection of a person in case of direct contact with live parts. No power consumption, operability is maintained when neutral conductor is broken. Independent contact position indicator.

Test circuit of the breaker remains operable within wide voltage range:

- 110 to 265 V for 2-pole version, - 200 to 460 V for 4-pole version.

Quick installation using the latch with double locking. Improved reliability of the selective assembly.Number of poles: 4

Primary current: 50

Leakage current type: EV000460

Short-circuit conventional residual current: 6

Rated surge voltage invariability: 6 Degree of protection (IP): EV006405 Mounting method: EV004369

Frequency: EV008013
Short-circuit breaking capacity (Icw): 6
Surge current capacity: 0,25
Max. cross section incoming cable: 50
Built-in depth: 74
Conditioned rated short-circuit current Iq: 6

Nominal rated current: 50 Nominal rated voltage: 400

Width in number of modular spacings: 4

Rated fault current: 0.30 Pret: 0,00 lei (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/bipolara-cu-protectie-diferentiala-rccb-vd1-63s-4p-50a-300ma-307191