

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



IEK BIPOLARA CU PROTECTIE DIFERENTIALA RCBO AVDT32EM V16 10MA

The AVDT32 RCCBs combine functions of automatic current breakers and type A electromechanic residual current breaker. Break current in protected circuit section in case of current earth leakage or overcurrent. React as on sinusoidal alternating residual current, and as pulsating direct current (type A), that allows to use it in buildings and domestic constructions with lot of household appliances. Does not have own energy consumption. Do not depend on the supply voltage, remain operational when the zero conductor breaks.

Protection against impulse overvoltage.

Convenient and reliable installation.

Connection variability: possible connection with FORK bus. Number of poles: 2

Number of protected poles: 1

Nominal rated voltage: 230

Leakage current type: EV000896

Width in number of modular spacings: 2

Max. cross section incoming cable: 25

Rated surge voltage invariability: 4

Frequency: EV008013

Degree of protection (IP): EV006405

Built-in depth: 71,5

Breaking capacity: 6.0

Ambient class: IEK V0000067

Moment of an inhaling of screws of contact clips: 2

Release characteristic: EV000074

Number of poles (total): 2

Nominal rated current: 16

Rated fault current: 0,01

Rated short-circuit breaking capacity EN 60898: 6

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/bipolara-cu-protectie-diferentiala-rcbo-avdt32em-v16-10ma-307293>