



Furnizor: **Sc Trivolt Distribution SRL** Reg. com.: J23/3300/2016 CIF: RO36421140

Adresa: Strada Apusului nr 3 (primul sens giratoriu Tehodor Pallady-Autostrada Soarelui), Catelu, İlfov

Banca: BRD

IBAN: RO34BRDE441SV13182234410



IEK MODULAR AUTOMATIC TRANSFER SELECTOR AVR-1 STANDARD 63A KARAT

Designed for automatic switching to backup power supply of three-phase AC electrical circuits. ATSs are used in industry, commercial and residential objects. AVR-1 STANDARD is equipped with circuit breakers BA47-60M with nominal current: 63A. If necessary, the circuit breakers can be independently replaced by installing VA with a different rated current.Compact solution.

Resistant to electromagnetic interference.

Energy saving: less than 5 W consumption.

Smooth regulation range.

Manual, remote and automatic switching. Upper threshold of ABP actuation voltage: 260

Height: 125 Depth: 121

Mechanical design group in accordance with GOST 17516.1: IEK V0000085

Environmental group in accordance with GOST IEC 60947-1: B

Operating voltage range: 175...265 Operating temperature range: -5...+40

Overload protector: 63

Utility category: IEK_V0000744

Classification by ability to respond to short-circuit currents in accordance with GOST IEC 60947-6-1: IEK_V0000745

Number of handle operating positions: 3

Number of poles: 3

Maximum number of conductors per clamp: ≤ 2 Moment of an inhaling of screws of contact clips: 2 Breaking capacity (IEC947, Icu, 400 V): 6.0 Lower threshold of ABP actuation voltage: 180

Nominal current: 63

Generator control relay nominal current: 3

Power consumption: ≤ 5 Connection capability: 1...25
Operation mode: IEK_V0000286
Switching modes: IEK_V0000748
Switching Control Method: IEK_V0000742

Degree of contamination in accordance with GOST IEC 60947-1: 2

Degree of protection in accordance with GOST 14254 (IEC 60529): EV006405 Type of built-in circuit breakers: 9.47-600

Type of conductors to attach: IEK_V0000746

Response characteristics from overcurrent type: IEK_V0000747

Width: 248

Pret: 0,00 lei (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/modular-automatic-transfer-selectoravr-1-standard-63a-karat-307316