

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



### **IEK MODULAR CONTACTORS KM KM63-11M AC**

KM type module contactors are intended for use in AC networks of 400 V (50 Hz) and serve for commutating low inductance loads with rated currents up to 63 A. They are applied for automation and control of various technological processes including that of lighting, ventilation and conditioning systems. Wide range of contactors with 2 or 4 normally open contacts.

Size compatibility with modular series devices.

Independent control coil supply - AC or DC.

Visual main contacts state indication.

High mechanical and electrical wear resistance.

Fast response (turning on - 20 ms, shutdown - 30 ms).

Bridge contacts provide double break at main contacts trip.

Low noise level. Rated operation current: 63 A

Number of normally open contacts: 1

Number of normally closed contacts: 1

Rated operating voltage: 230 V

Width in number of modular spacings: 2

Conditioned rated short-circuit current  $I_q$ : 3 kA

Rated surge voltage invariability: 4 kV

Voltage type (operating voltage): EV000460

Rated excitation voltage: 230 V

Degree of protection (IP): EV006405

Utility category:  $\text{D}\text{D}_j\text{-1}$ ,  $\text{D}\text{D}_j\text{-7D}^\circ$

Voltage type (excitation voltage): EV000460

Max. incandescent lamp load: -

Max. load fluorescent lamp: -

Number of modular spacings: 2

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialeelectric.ro/modular-contactors-km-km63-11m-ac-307348>