



Furnizor: **Sc Trivolt Distribution SRL** Reg. com.: J23/3300/2016 CIF: RO36421140 Adresa: Strada Apusului nr 3 (primul sens giratoriu Tehodor Pallady-Autostrada Soarelui), Catelu, Ilfov Banca: BRD IBAN: RO34BRDE441SV13182234410

IEK MODULAR SEPARATOR VRM-3 3P 80A

VRM IEK modular circuit breakers are designed for switching mixed and inductive loads in AC circuits, as well as for switching to backup power supply of AC electrical circuits.Easy installation/removal on DIN rail. Two fixed positions of the handle. High rated currents: up to 125A. Possibility to use together with adapter and remote handle for door control.Switching function: RV001251 Number of change-over contacts: 0 Number of contacts as change-over contact: 0 Number of poles: 3 Nominal rated current: 80 Nominal rated voltage: 690/400 Rated switching capacity: Voltage type: EV000509 Colour calotte: EV000206 Lamptype: EV008336 Width in number of modular spacings: 7,8 Degree of protection (IP): EV006405 Mains frequency: 50 Mains frequency: 50 Rated surge voltage invariability: 8 Nominal short-term maintained current during 1s Icw : 1500 Mechanical wear resistance: 10000 Electric wear resistance: 7500 Max. conductor cross section: 35 Operating temperature researce 25 40 Operating temperature range: -25...40 Utility category: IEK_V000709 Nominal DC operating voltage: 440/230 Height: 100 Width: 141 Depth: 87 Number of contacts as normally open contact: 0 Number of contacts as normally closed contact: 0 Connection capacity of contact clamps: 1,5...35 Pret: 0,00 lei (TVA inclus) Detalii online: https://www.materialeelectrice.ro/modular-separator-vrm-3-3p-80a-307466