

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



IEK AUXILIARY CONTACT DKM-125 (DKM-32) MASTER

DKm auxiliary contact is designed for giving out a signal about the CB power contacts status (switched on/off).Ease of use.

The ability to install independently in production by the customer.Compatibility: D'D88

ŃĐµŃ€Đ,Đ, MASTER

Nominal rated voltage: AC: 230/400; DC: 220

Number of contacts as change-over contact: 2

Number of contacts as normally open contact: 1

Number of contacts as normally closed contact: 1

Nominal current AC-15 with nominal operating voltage 230V: 0.50

Nominal current AC-15 with nominal operating voltage 400V: 0.50

Nominal current DC-13 with nominal operating voltage 230V: 0.15

Conditional heat current of additional contact: 1.0

Rated insulation voltage U_i : 690

Type of electric connection: EV000415

Width: 25.7

Height: 37.5

Depth: 48.3

Rated operation current I_e at AC-15, 230 V: 0.5

Mounting method: EV003964

Conductor cross section: 0,2

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/auxiliary-contact-dkm-125-dkm-32-master-307504>