

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



IEK SHUNT RELEASE RNM-125 (RNM-32) 220V MASTER

RNm shunt trip is used for remote shutting down of MCCB.Ease of use.
The ability to install independently in production by the customer.Operating voltage
range: (0,7...1,1)N...Ue
Operating temperature range: -40...+60
Number of contacts as normally open contact: 0
Number of contacts as normally closed contact: 0
Number of contacts as change-over contact: 0
End value adjustment range undelayed short-circuit release: -
Initial value of the undelayed short-circuit release - setting range: -
Rated control supply voltage Us at DC: -
Rated control supply voltage Us at AC 50HZ: 230; 400
Nominal rated voltage: 230; 400
Compatibility: ĐĐ88 NĐµN€Đ Đ, MASTER
Voltage type for actuating: EV000460
Mains frequency: 50
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialeelectric.ro/shunt-release-rnm-125-rnm-32-220v-master-307515>