



Furnizor: **Sc Trivolt Distribution SRL** Reg. com.: J23/3300/2016 CIF: RO36421140 Adresa: Strada Apusului nr 3 (primul sens giratoriu Tehodor Pallady-Autostrada Soarelui), Catelu, Ilfov Banca: BRD IBAN: RO34BRDE441SV13182234410

IEK INTRERUPATOR GENERAL MCCB VA44 33 3P 63A 15KA Moulded case circuit breakers (MCCB) VA44 IEK are meant to conduct current in normal mode and current shutdown in case of short circuits, overload, unacceptable drops of stress, as well as for operational connect and disconnect of electrical circuits. Designed for operation in electrical installations with rated operating voltage up to 400 V and rated currents from 25 to 630A. Meet the requirements of GOST R 50030.2.Simple 0 **∂** iEK self-installation of additional devices universal (suitable for VA44 and VA88): emergency contact; additional contact; - shunt release; - undervoltage release; - combined contact. Double insulation. Reliable protection against overcurrents. Compact dimensions. Economical solution.Weight: 0.745 Position of connection for main current circuit: EV009502 Height: 120.0 Depth: 59.0 Setting range over-current release: 10 In Additional equipment attached at delivery: EV000154 Version: EV005518 Number of auxiliary contacts as normally closed contact: 0 Number of auxiliary contacts as normally open contact: 0 Number of auxiliary contacts as change-over contact: 0 Number of poles: 3 Device construction: EV009311 Mechanical wear resistance with maintenance: 5000 Rated surge voltage invariability: 8 Rated voltage: 400 Rated insulation voltage Ui: 400 Rated short-circuit breaking capacity Icu at 400 V, 50 Hz: 15 Rated permanent current Iu: 63 Nominal operating max breaking capacity: 9 Nominal rated voltage: 400 Nominal rated current: 63 Degree of protection (IP): EV006410 Ambient temperature: -30...50 Connection type main current circuit: EV000415 Type of control element: EV000421 Mains frequency: 50 Width: 76.2 Pret: 235,54 lei (TVA inclus) Detalii online: https://www.materialeelectrice.ro/intrerupator-general-mccb-va44-33-3p-63a-15ka-307608