

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



### **IEK INTRERUPATOR GENERAL MCCB VA44-37 3P 315A 35KA**

Moulded case circuit breakers (MCCB) VA44 IEK are meant to conduct current in normal mode and current shutdown in case of short circuits, overload, unacceptable drops of stress, as well as for operational connect and disconnect of electrical circuits. Designed for operation in electrical installations with rated operating voltage up to 400 V and rated currents from 25 to 630A. Meet the requirements of GOST R 50030.2.Compact dimensions.

Pole configuration.

Installation in any position (vertical/horizontal).

Universal accessories (used for VA88 and VA44).Weight: 2.900

Position of connection for main current circuit: EV009502

Height: 180.0

Depth: 133.5

Setting range over-current release: 10 In

Version: EV005518

Number of auxiliary contacts as normally closed contact: 0

Number of auxiliary contacts as normally open contact: 0

Number of auxiliary contacts as change-over contact: 0

Number of poles: 3

Device construction: EV009212

Mechanical wear resistance with maintenance: 7000

Rated surge voltage invariability: 8

Rated voltage: 400

Rated insulation voltage  $U_i$ : 750

Rated short-circuit breaking capacity  $I_{cu}$  at 400 V, 50 Hz: 35

Rated permanent current  $I_u$ : 315

Nominal operating max breaking capacity: 18

Nominal rated voltage: 400

Nominal rated current: 315

Power consumption: 60

Degree of protection (IP): EV006410

Ambient temperature: -30...50

Connection type main current circuit: EV000415

Type of control element: EV000421

Mains frequency: 50

Width: 120.0

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialeelectric.ro/intrerupator-general-mccb-va44-37-3p-315a-35ka-307616>