



Furnizor: **Sc Trivolt Distribution SRL** Reg. com.: J23/3300/2016 CIF: RO36421140 Adresa: Strada Apusului nr 3 (primul sens giratoriu Tehodor Pallady-Autostrada Soarelui), Catelu, Ilfov

Banca: BRD

IBAN: RO34BRDE441SV13182234410



IEK SEPARATOR DISCONNECTOR PE19-35-31140 250A

The disconnectors of RE-19 series are designed for conducting the rated current and not frequent non-automatic switching of circuits without load of rated voltage up to 1000 VAC and frequency 50, 60 Hz. RE-19 IEK can be used in switchgears with rated currents from 250 to 1600 A.Convenient installation and operation.

Low power losses due to use of high-quality materials.

Visible circuit gap.

Wide range of control handles.

Copper and aluminum conductors can be connected. Rated permanent current Iu: 250

Max. rated operation voltage Ue AC: 660

Conditioned rated short-circuit current Iq: 14

Number of poles: 3

Device construction: EV009211 Type of control element: EV004094

Connection type main current circuit: EV008864

Degree of protection (IP), front side: EV006404
Degree of protection (IP): EV006404
Rated insulation voltage Ui: 660 Rated operating voltage Ue: 660

Nominal operating voltage Ue -DC-20 V: 440 Manual actuator handle type: IEK_V0000053 Pret: 1 004,87 lei (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/separator-disconnector-pe19-35-31140-250a-307755