



Furnizor: **Sc Trivolt Distribution SRL** Reg. com.: J23/3300/2016 CIF: RO36421140

Adresa: Strada Apusului nr 3 (primul sens giratoriu Tehodor Pallady-Autostrada Soarelui), Catelu, Ilfov

Banca: BRD

IBAN: RO34BRDE441SV13182234410



IEK JOYSTICK LA167-PA12 2 2 POSITION 2NC FIXATION NEGRU

The joystick is designed to provide intuitive control of the equipment. Easy installation in standard 22 mm seats provides a variety of applications of the control device in various variations of control and monitoring equipment. High wear resistance.

Fast closing/opening.

Versatility and a wide range. Number of poles: 1

Max. rated operation voltage Ue AC: 400 Rated permanent current Iu: 7.5 Number of switch positions: 2 Device construction: EV002104

Type of control element: IEK V0000601

Degree of protection (IP), front side: EV006415 Number of auxiliary contacts as normally open contact: 0 Connection type main current circuit: EV000415

Number of auxiliary contacts as normally closed contact: 2 Rated insulation voltage Ui: 660 Nominal heat current Th: 10

Nominal heat current Th: 10
Rated operation current Ie at AC-15, 230 V: 7,5
Nominal operating current Ie at AC-15 400V: 4,5
Electric wear resistance: 0,3
Mechanical wear resistance: 0,6
Degree of Protection - IP Side of Contacts: EV006404
Ambient temperature: -10...+40
Nominal operating voltage AC contacts: 110; 230; 400; 660
Nominal operating voltage DC contacts: 24; 48; 110; 220; 440
Diameter openings: 22 0

Diameter openings: 22.0 Nominal Attachment Capacity: 2Ñ...2,5

Width: 40.0 Height: 30.0

Depth: 148.0 Type of switch: RV001225 Pret: 0,00 lei (TVA inclus)

 $\label{lem:decomposition} \textbf{Detalii online:} \ https://www.materialeelectrice.ro/joystick-la167-pa12-2-2-position-2nc-fixation-negru-312065$