IEK ASSEMBLABLE DISTRIBUTION EMPTY ENCLOSURE VRU 1800X600X450 IP31 SMART

Lead-in distribution empty enclosuresare intended for electric power supply, accounting and distribution with 380/220 V voltage in three-phase AC networks (frequency - 50 Hz) as well as for protecting the lines at short circuits and overloads. They are also designed for often operation actuation and power-offs.High technological effectiveness and ease of assembly.
The ability to install trim panels.
Ease of installation, transportation and storage.
A wide range of accessories, the possibility of dividing space into compartments.
The ability to install accessories at different depths (interval 20 mm), width (interval 25mm) and height (interval 25 mm).
Improved design of the case provides more rational use of the working space.
Removable side panels provide easy access to the equipment during installation.
High-quality outer coating.
Reversible door.
Profile on the door for installation of lighting equipment.
Increased corrosion resistance.
Buildings in the blocks.
High level of electrical safety.
Pocket for documents.
Earthing studs on the door.
Certificate of conformity.Degree of protection (IP): EV006411
Ambient class: IEK_V0000009
Primary current: 630
Material housing: EV000179
RAL-number: 7035
Height: 1800
Width: 600
Depth: 450
Built-in depth: -
Type of cover: EV000116
Weight: 54,3
Surface Billing: IEK_V0000104
Door opening angle: 120
Type of installation: IEK_V0000113
Metal thickness: 1,4
Number of modules: -
Type of door: EV002646
Plate thickness cabinet: 1.4
Plate thickness door/cover: 1,4
Cover model: EV000494
Pret: 0,00 lei (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/assemblable-distribution-empty-enclosure-vru-1800x600x450-ip31-smart-308594