

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



IEK INPUT TERMINAL PENTRU KVM MODULAR EQUIPMENT 4-25MM2 (DIRECT INPUT EXTENDED)

Designed to create feed-through connections of groups of circuit breakers, the power to the connecting bars and terminal clamps of modular devices in the electrical boards and electrical installations up to 400 watts. Convenient carrying of power to modular devices. Wide range of operating temperatures: -40...+50 °C.

Possibility to connect large cross-section conductors up to 50 mm².

Material of current-carrying parts of terminals - copper. Connectable conductor cross section solid-core: 4...25

Connectable conductor cross section multi-wired: 4...25

Rated current In: 100

Nominal rated voltage: 400

Type of electrical connection 2: EV000415

Connection position: EV000644

Number of poles: 1

Number of clamp positions per pole: 1

Mounting method: EV005276

Material insulation body: EV000139

Operation temperature: -45...+50

Width/grid dimension: 13.5

Length: 45,5

Colour: EV000270

Nominal operating AC voltage U_e: 400

Nominal DC operating voltage U_e: 220

Nominal frequency: 50

Rated insulation voltage U_i: 415

Max. conductor cross section: 25

Material clamp: EV000149

Nominal Attachment Capacity: 4...25

Tightening torque Nm at conductor section: 2,5

Quantity in the kit: 10

Minimum section: 10.0

Attachment screw: Dø8

Current-carrying part material: EV000138

Nominal insulation voltage: 415

Relative air humidity: 50% D_zN_zD, t=40°C

Refinement: EV001481

Colour housing: EV000271

: EV000138

Type of electrical connection 1: EV000415

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/input-terminal-pentru-kvm-modular-equipment-4-25mm2-direct-input-extended-308969>