

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



### **IEK Î€ÇENÎ€ NEUTRAL BUS PENTRU A DIN-RAIL IN 2X15 CASING OF GROUP**

These bars are made of high-quality latten alloy, insulated back panel and transparent protective cover are made of selfextinguishing plastic. Enclosed neutral bus bars are used for completing panel equipment for connecting a neutral conductor (neutral operating bus), a grounding wire and phase conductors. Mounting methods: - onto a 35 mm DIN-rail; - with two screws onto the distribution box panel. Each bus is separately insulated. Cross-module are manufactured with two or four buses suitable for currents limited to 100 and 125 A.Made of high quality brass, the insulating back panel and transparent protective cover are made of self-extinguishing plastic.Height: 45

Width: 132

Depth: 51

Number of poles: 1

Number of clamp positions per pole: 15

Max. rated current: 125

Conductor cross section flexible (fine-strand) with cable end sleeve: -

Conductor cross section solid (solid, stranded): -

Pret: 56,18 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/n-neutral-bus-pentru-a-din-rail-in-2x15-casing-of-group-308972>