

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



IEK ÎCENÎE NEUTRAL BUS PENTRU A DIN-RAIL IN 4X7 CASING OF GROUP

These bars are made of high-quality latten alloy, insulated back panel and transparent protective cover are made of selfextinguishing plastic. Enclosed neutral bus bars are used for completing panel equipment for connecting a neutral conductor (neutral operating bus), a grounding wire and phase conductors. Mounting methods: - onto a 35 mm DIN-rail; - with two screws onto the distribution box panel. Each bus is separately insulated. Cross-module are manufactured with two or four buses suitable for currents limited to 100 and 125 A. Made of high quality brass, the insulating back panel and transparent protective cover are made of self-extinguishing plastic. Height: 87

Width: 65

Depth: 50

Number of poles: 3

Number of clamp positions per pole: 7

Max. rated current: 100

Conductor cross section flexible (fine-strand) with cable end sleeve: -

Conductor cross section solid (solid, stranded): -

Pret: 57,21 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/n-neutral-bus-pentru-a-din-rail-in-4x7-casing-of-group-308973>