



Furnizor: **Sc Trivolt Distribution SRL** Reg. com.: J23/3300/2016 CIF: RO36421140 Adresa: Strada Apusului nr 3 (primul sens giratoriu Tehodor Pallady-Autostrada Soarelui), Catelu, Ilfov Ranca: RRD

Banca: BRD IBAN: RO34BRDE441SV13182234410



IEK CENTRAL JUMPER PENTRU KWI-6MM2 2PIN

Jumpers (combs) are used for the electrical connection of rows of screw-type terminal Jumpers (combs) are used for the electrical connection of rows of screw-type terminal assemblies (KWI terminals) in distribution systems. They are installed in the center of the terminal in the corresponding grooves of the current-carrying plates by screwing the connecting screw into the busbar. Made as steel plates with 2, 3 or 10 leads.Rated operating current and voltage: 24 to 85A / up to 800V.

Wide operating temperature range: -60°C to +110°C.

Excess temperature test (not more than 45°C).

Test for short-term withstand current of 120A per 1mm2 for 1 second.

Voltage drop test (not more than 3.2mV). Model: EV005494

Number of bridged clamps: 2 Rated current In: 50

Mounting method: EV001790 Colour: EV000154

Pret: 0,00 lei (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/central-jumper-pentru-kwi-6mm2-2pin-