



Furnizor: **Sc Trivolt Distribution SRL** Reg. com.: J23/3300/2016 CIF: RO36421140 Adresa: Strada Apusului nr 3 (primul sens giratoriu Tehodor Pallady-Autostrada Soarelui), Catelu, Ilfov

Banca: BRD

IBAN: RO34BRDE441SV13182234410



IEK CORRUGATED HDPE PIPE WITH A BROACH TOOL D20 ORANGE (100 M)

Orange HDPE corrugated pipes are designed for laying them in the information power and low-current electrical communication systems. HDPE corrugated pipes sustain combustion, so their scope of application is limited to laying hidden in nonflammable materials. Installation conditions: for nonexposed installation in the conduit of the walls, in ceilings, in floor layers made of non-combustible materials. Corrugated pipe HDPE

orange color is characterized by high elasticity and impact strength.

The wide temperature range allows installation and operation of corrugated HDPE pipes at temperatures from -40°C to +90°C.Degree of protection (IP): EV006415

Colour: EV000236 RAL-number: 2004 Outer diameter: 20 Material: EV003904

Operating temperature: -40...90 Compressive strength: 125 Nominal diameter: 20 Inner diameter: 14.5

Bending strength: EV000995 Nominal electric insulation strength: 250

Pret: 0,00 lei (TVA inclus)

 $\begin{tabular}{ll} \textbf{Detalii online:} & \textbf{https://www.materialeelectrice.ro/corrugated-hdpe-pipe-with-a-broachtool-d20-orange-100-m-310104} \\ \end{tabular}$