

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



IEK CORRUGATED HDPE PIPE D25 ORANGE HEAVY (50 M)

Corrugated pipe from HDPE (high density polyethylene) of heavy type are designed for routing information power and low-voltage electrical equipment of concealed type (inside the fireproof structures, in conduits and floor screed of non-combustible materials, to fill in concrete) in offices and residential premises in the monolithic concrete building, industrial and administrative buildings, the construction or reconstruction. It can withstand high mechanical loads, which allows it to be used for pouring into concrete.

The presence of the probe makes it easy to stretch the cable and provides ease of installation.

It is resistant to moisture and aging.

Mechanical strength (compressive strength): 350N more than 5 cm at 20°C.

Dielectric strength of at least 2000V (50 Hz, for 15 minutes).

Tensile strength: 200N. Insulation resistance: not less than 100 megohm (500V, for 1 min).

Degree of protection: IP55 according to GOST 14254. Degree of protection (IP):

EV006415

Colour: EV000236

RAL-number: 2004

Outer diameter: 25

Material: EV003904

Operating temperature: -40...90

Compressive strength: 750

Nominal diameter: 25

Inner diameter: 18.6

Bending strength: EV000995

Nominal electric insulation strength: 250

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/corrugated-hdpe-pipe-d25-orange-heavy-50-m-310130>