



Furnizor: **Sc Trivolt Distribution SRL** Reg. com.: J23/3300/2016 CIF: RO36421140 Adresa: Strada Apusului nr 3 (primul sens giratoriu Tehodor Pallady-Autostrada Soarelui), Catelu, Ilfov

Banca: BRD

IBAN: RO34BRDE441SV13182234410



IEK DOZA ANTIFOC 150X110X85MM 6P 10MM2 IP44 SMOOTH **WALLS**

Fire-resistant mounting boxes are used for open wiring for branching of wires and cables, as well as for additional protection of switching units. Special solution for the organization of fire-resistant cable lines with fire resistance class of E15-E90 when laying power and information cables. Correspond to GOST R 53316-2009 "Cable lines. Survival under fire conditions".Reliable and durable plastic from a special composition of thermoplastics with flame retardant additives.

Fire resistance limit: E15-E90.

Terminal plate: fire-resistant steatite ceramics.

Galvanized fasteners included.

Setting the box on a metal cable support system with special circuit boards galvanized

IEK.

Cable section: from 0.5 mm2 to 16 mm2. Number of connection clamps: 6

Max. conductor cross section: 10.0

Length: 150.0 Width: 110.0 Depth: 85.0

Mounting method: EV000384

Number of inlets: 0

Material: EV000934 Colour: EV000236

Degree of protection (IP): EV006418 Cover attachment: EV000115 Rated insulation voltage Ui: 450 Nominal voltage: 230/400

Flammability category in accordance with GOST 28157: IEK_V0000493 Pret: 0,00 lei (TVA inclus)

 $\begin{tabular}{ll} \textbf{Detalii online:} & \textbf{https://www.materialeelectrice.ro/doza-antifoc-} 150x110x85mm-6p-10mm2-ip44-smooth-walls-310177 \end{tabular}$