

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



#### **IEK TERMOCONTRACTIBIL PTK 3X16-25 1KW**

Designed for sealing of termination roots of multi-core power cables with paper oil-impregnated insulation, plastic insulation, cross-linked polyethylene insulation. Inner surfaces of base and branches of multiple cable joint are coated with adhesive thermomelting layer that ensures perfect sealing after shrinkage. Depending on number of cable cores, the joints can be of 2-, 3-, 4- and 5-branch type. An adhesive layer is applied to the inner surface of the base and fingers of the glove, which melts during shrinkage and provides complete waterproofing of the joint.

Gloves are resistant to ultraviolet light and any weather conditions.

Gloves can be used when inserting SIP lines into pipes and cable channels. Model: EV008815

Nominal cross section: 16...25

Diameter shaft before shrink:  $\geq 35$

Diameter shaft after shrink:  $\leq 15$

Total length after shrink: 90

Inner diameter finger before shrink:  $\geq 14$

Inner diameter finger after shrink:  $\leq 4,5$

Operation temperature: -55...125

AC 50 Hz operating voltage: 1000

Tensile strength:  $\geq 13$

Volumetric electrical resistance:  $\geq 1\tilde{N}...10^{16}$

Min shrinkage start temperature: 110

Min full shrinkage temperature: 150

Length of cable part: 68

Length of fingers: 22

Total length: 90

Mounting temperature: -10...50

Wall thickness before heat shrinkage:  $\geq 2,2/\geq 2,0$

Type: EV004267

Pret: 14,27 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/termocontractibil-ptk-3x16-25-1kw-310494>