


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<p style="text-align: center;">IEK TERMOCONTRACTIBIL PTK 5X150-240 1KW</p> <p>Designed for sealing of termination roots of multi-core power cables with paper oil-impregnated insulation, plastic insulation, cross-linked polyethylene insulation. Inner surfaces of base and branches of multiple cable joint are coated with adhesive thermomelting layer that ensures perfect sealing after shrinkage. Depending on number of cable cores, the joints can be of 2-, 3-, 4- and 5-branch type. An adhesive layer is applied to the inner surface of the base and fingers of the glove, which melts during shrinkage and provides complete waterproofing of the joint. Gloves are resistant to ultraviolet light and any weather conditions. Gloves can be used when inserting SIP lines into pipes and cable channels. Model: EV008817</p> <p>Nominal cross section: 150...240 Diameter shaft before shrink: ≥ 100 Diameter shaft after shrink: ≤ 44 Total length after shrink: 175 Inner diameter finger before shrink: ≥ 34 Inner diameter finger after shrink: ≤ 11 Operation temperature: -55...125 AC 50 Hz operating voltage: 1000 Tensile strength: ≥ 13 Volumetric electrical resistance: $\geq 1\text{N} \dots 10^{16}$ Min shrinkage start temperature: 110 Min full shrinkage temperature: 150 Length of cable part: 125 Length of fingers: 50 Total length: 175 Mounting temperature: -10...50 Wall thickness before heat shrinkage: $\geq 3,0 / \geq 3,0$ Type: EV004267 Pret: 44,54 lei (TVA inclus)</p> <p>Detalii online: https://www.materialeelectrice.ro/termocontractibil-ptk-5x150-240-1kw-310501</p>
---	---