


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

| | |
|--|---|
|  | <p align="center"><u>IEK TERMOCONTRACTIBIL KV(N)TP 3X150/240CU IZOLATIE DIN HARTIE 1KV</u></p> <p>KV(N)tp-1 heat-shrink sleeve is designed for termination of aluminum or copper conductors of cables with impregnated-paper insulation for voltages up to 1 kV: AAG-1, AASh-1, AAB-1, AAP-1, AABSh-1, AAPSh-1, ASG-1, AASSh-1, ASBSh-1, SG-1, SSh-1, SBSh-1, SB-1, SP-1, SK-1, SBG-1, SPG -1, their equivalents and versions. Perfectly leak-tight sleeve design due to:</p> <ul style="list-style-type: none">- use of high-quality two-layer heat-shrink materials with adhesive thermomelting coating on inner surfaces of tubes and multiple cable joints;- oil-resistant tubes put over phase insulation of cable conductors;- use of special sealant for hydrochemical protection, applied over cable sheath and armor grounding assembly. <p>The sleeve is of universal type and can be used both outdoors and indoors in compartments with any level of humidity.</p> <p>The cable sheath and armor grounding set is available for ordering with materials suitable for soldering or with constant-force springs made from high-quality stainless steel AISI 301 with high content of chromium and nickel. Suitable for: EV009729</p> <p>Model: EV004267 Voltage row: EV004258 Nominal cross section: 150...240 Type of insulation material: IEK V0000183 Installation Type: IEK V0000187 Complete set: IEK V0000188 Number of cores wiring: 3 Tip Type: IEK V0000189 Attachment of the grounding bus to the cable: IEK_V0000192 Nominal voltage: 1 Material: IEK V0000193 Min full shrinkage temperature: 120 Operating temperature range: -45...+50 Shrink rate: EV009535 Grounding bus Material: EV004186 External grounding bus attachment: IEK_V0000194 Number of conductors: 3 Pret: 377,41 lei (TVA inclus)</p> <p>Detalii online: https://www.materialeelectrice.ro/termocontractibil-kv-n-tp-3x150-240cu-izolatie-din-hartie-1kv-310505</p> |
|--|---|