

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<u>IEK TERMOCONTRACTIBIL STT(TP)3X16/25CU IZOLATIE DIN HARTIE 1KW</u> Stt(tp)-1 heat-shrink sleeve is designed for connection of aluminum or copper conductors of cables with impregnated-paper insulation for voltage 1 kV: AAG-1, AASh-1, AAB-1, AAP-1, AABSh-1, AAPSh-1, ASG-1, AASSh-1, ASBSh-1, SG-1, SSh-1, SBSH-1, SB-1, SP-1, SK-1, SBG-1, SPG -1, their equivalents and versions. The sleeves can be installed directly in the ground, tunnels and channels and also outdoors: on trestles, cable shelves, etc. Perfectly leak-tight sleeve design due to: - use of high-quality two-layer heat-shrink materials with adhesive thermomelting coating on inner surfaces of tubes and multiple cable joints; - oil-resistant tubes put over phase insulation of cable conductors; - use of special sealant for hydrochemical protection, applied over cable sheath and armor grounding assembly. Voltage row: EV004258 Model: EV004267 Number of conductors: 3 Nominal cross section conductor: 16...25 Suitable for: EV000154 Type of insulation material: IEK V0000183 Installation Type: IEK V0000187 Complete set: IEK V0000188 Connector Type: IEK V0000189 Attachment of the grounding bus to the cable: IEK V0000192 Nominal voltage: 1 Material: IEK V0000193 Min full shrinkage temperature: 120 Operating temperature range: -45...+50 Shrink rate: EV009535 Pret: 325,58 lei (TVA inclus) Detalii online: https://www.materialeelectrice.ro/termocontractibil-stt-tp-3x16-25cu-izolatie-din-hartie-1kw-310533
--	--